



# Tape & Reel Packaging Standards



[www.onsemi.com](http://www.onsemi.com)

# Tape and Reel Packaging Standards

---

BRD8011/D  
Rev. 15b, January–2014

© SCILLC, 2014  
Previous Edition @ April, 2013  
“All Rights Reserved”



**ON Semiconductor®**


<http://onsemi.com>

Micro8 is a trademark of International Rectifier.

PowerFLEX is a trademark of Texas Instruments Incorporated.

POWERMITE is registered trademark of and used under a license from Microsemi Corporation.

MicroLeadless is a trademark of Semiconductor Components Industries, LLC (SCILLC).

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# ON Semiconductor Tape and Reel Packaging Standards

---

## In Brief . . .

This booklet has been offered to assist those looking to coordinate packaging specifications with assembly line requirements. Additionally, dimensional and ordering information is supplied for those discrete devices that take the form of axial-leaded parts.

	Page
Surface Mount	
Packaging Standards . . . . .	4
Ordering Information . . . . .	7
Former CMD Tape and Reel Standards . . . . .	10
Product Orientation . . . . .	13
Dimension Standards . . . . .	22
Thru Hole	
TO-92 Radial Tape Specifications . . . . .	27
(Fan Fold Box and on Reel)	
Axial-Leaded	
Lead Tape Standards for Axial-Lead	
Components . . . . .	32
Information for Using	
Surface Mount Packages . . . . .	33
Humidity Indicator Card . . . . .	38

# Tape and Reel Packaging Standards

Embossed Tape and Reel is used to facilitate automatic pick and place equipment feed requirements. The tape is used as the shipping container for various products and requires a minimum of handling. The antistatic/conductive tape provides a secure cavity for the product when sealed with the “peel-back” cover tape.

- Two Reel Sizes Available (7” and 13”)
- Used for Automatic Pick and Place Feed Systems
- Minimizes Product Handling
- EIA 481, -1, -2 Series
- DFN/QFN covers all other Thickness Designators for these packages; i.e. WDFN, UDFN, XDFN, etc..
- 8 mm Tape: 6-Bump, 9-Bump, 10-Bump, MicroLeadless™, ChipFET, DFN/QFN packages ≤ 3.3x3.3, DSN, Flip-Chip, SOD-123, SC-59, SC-70, SC-74, SC-74A, SC-75, SC-82, SC-82AB, SC-88, SC-88A, SC-89, SOD-123, SOD-323, SOD-523, SOD-723, SOD-923, SOT-143, SOT-23, SOT-23L, SOT-323, SOT-353, SOT-553/563, SOT-723, SOT-883, SOT-1123, TSOP-5, TSOP-6, US8, WLCSP-4, WLCSP-5, X3DFN, XLLGA
- 12 mm Tape: DFN/QFN packages > 3.3x3.3 and ≤ 7x7, FCBGA-16, Micro10, Micro8™, PowerFLEX™, POWERMITE™, QSOP-16, SMA, SMB, SO-8 (SOIC 8), SOT-223, SOT-89, SSOP-8, TSSOP-8, TSSOP-10, TSSOP-14, TSSOP-16
- 16 mm Tape: DFN/QFN packages > 7x7, DPAK, FCBGA-16, PLCC-20, QSOP-24, SMC, SO-14 (SOIC 14), SO-16 (SOIC 16), SO-16 Wide (SOIC 16W), SOIC-EIAJ8, SOIC-EIAJ14, SOIC-EIAJ16, SOP-16, SSOP-14 Wide, SSOP36-EP, TQFP-32, TSSOP-20
- 24 mm Tape: D<sup>2</sup>PAK, FCBGA-81, LQFP-52, LQFP-64, PLCC-28, SO-18 Wide (SOIC 18W), SO-20 Wide (SOIC 20W), SO-24 Wide (SOIC 24W), SOEIAJ-20, SSOP36-EP (Non-standard), TQFP-52, TQFP-64, TSSOP-48
- 32 mm Tape: PLCC-44, PLCC-52, SO-28L Wide (SOIC 28W), SO-28 Wide (SOIC 28W), SO-32 Wide (SOIC 32W),
- 44 mm Tape: PLCC-98, PLCC-84
- For Leadless Package Pin 1 Orientation, please see Figure 39 (Effective January 2007).

Use the standard device title and add the required suffix as listed in the option table on the following page. Note that the individual reels have a finite number of devices depending on the type of product contained in the tape. Also note the minimum lot size is one full reel for each line item, and orders are required to be in increments of the single reel quantity.

## Embossed Tape and Reel Ordering Information

Package	Tape Width mm	Pitch mm (Dimension P <sub>1</sub> ) (inch)	Reel Size		Devices Per Reel and Min Order Quantity	Tape and Reel Suffix	Fig No	Page No
			(mm)	(in)				
6-Bump (1.489x0.989)	8	4.0 ± 0.1 (0.158 ± 0.004)	178	7	3,000	T1 – TMOS	7	14
9-Bump (1.489x1.489)	8	4.0 ± 0.1 (0.158 ± 0.004)	178	7	3,000	T1 – TMOS	7	14
10-Bump	8	4.0 ± 0.1 (0.158 ± 0.004)	178	7	3,000	T1 – Discrete	7	14
Axial Leaded	See Axial Leaded package standards beginning on page 27							
ChipFET	8	4.0 ± 0.1 (0.158 ± 0.004)	178	7	3,000	T1 – TMOS	11	15
D <sup>2</sup> PAK 3 Lead	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	800	R4 Analog T4 – Discrete	1	13
D <sup>2</sup> PAK 5 Lead	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	800	R4 – Analog T4 – Discrete	1	13
D <sup>2</sup> PAK 7 Lead	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	750	R7 – Analog	1	13
DFN/QFN ≤ 1.4x1.4mm	8	2.0 ± 0.1 (0.079 ± 0.004)	178	7	See Data Sheet	Various	37–39	19,20
DFN/QFN ≤ 3.3x3.3mm	8	4.0 ± 0.1 (0.158 ± 0.004)	178	7	See Data Sheet	See Data Sheet	37–39	19,20
	8	4.0 ± 0.1 (0.158 ± 0.004)	330	13	See Data Sheet	See Data Sheet		
DFN/QFN ≥ 3.0x3.0mm and ≤ 7x7mm	12	8.0 ± 0.1 (0.315 ± 0.004)	178	7	See Data Sheet	See Data Sheet	37–39	19,20
	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	See Data Sheet	See Data Sheet		
DFN/QFN 7x7mm	12	16.0 ± 0.1 (0.630 ± 0.004)	178	7	See Data Sheet	See Data Sheet	37–39	19,20
	12	16.0 ± 0.1 (0.630 ± 0.004)	330	13	See Data Sheet	See Data Sheet		
DFN/QFN 9x9mm	16	12.0 ± 0.1 (0.471 ± 0.004)	178	7	See Data Sheet	See Data Sheet	37–39	19,20
	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	See Data Sheet	See Data Sheet		
DFN/QFN 10.5x10.5mm	16	16.0 ± 0.1 (0.630 ± 0.004)	178	7	See Data Sheet	See Data Sheet	37–39	19,20
	16	16.0 ± 0.1 (0.630 ± 0.004)	330	13	See Data Sheet	See Data Sheet		
DO–41	79	5.08 ± 0.508	356	14	5,000	RL – Discrete	N/A	32
DPAK	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,800	RL – Discrete	4	13
DPAK	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	T4, T5 – Discrete RK, T5 – Analog	2, 3	13
DSN	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	5,000	T5 – Discrete	6	14
FCBGA–16	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500/500	R2 – Clock & Data Mgmt	36	19
FCBGA–49	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000/500	R2 – Clock & Data Mgmt	36	19
FCBGA–81	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,500/500	R2 – Clock & Data Mgmt	36	19
Flip–Chip	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	N/A	N/A
LQFP – 48	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	R48 – Analog	8	14
LQFP–32	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1800 or 2000	R2 – Analog, Clock & Data Mgmt	8	14
LQFP–52	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	1,500	R2 – Clock & Data Mgmt	8	14
LQFP–64	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	1,500	R2 – Clock & Data Mgmt	8	14
Micro10	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	4,000	R2 – Analog, Discrete	32	18
Micro8™	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2, T – Analog	32	18
Micro8	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	4,000	R2 – Analog, Discrete	32	18

## Embossed Tape and Reel Ordering Information

Package	Tape Width mm	Pitch mm (Dimension P <sub>1</sub> ) (inch)	Reel Size		Devices Per Reel and Min Order Quantity	Tape and Reel Suffix	Fig No	Page No
			(mm)	(in)				
PLCC-20	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,000	R2 – Clock & Data Mgmt	9	14
PLCC-28	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	500	R2 – Clock & Data Mgmt	9	14
PLCC-44	32	24.0 ± 0.1 (0.942 ± 0.004)	330	13	500	R2 – Clock & Data Mgmt, Analog	9	14
PLCC-44	32	24.0 ± 0.1 (0.942 ± 0.004)	330	13	500	R44 – Analog	9	14
PLCC-52	32	24.0 ± 0.1 (0.942 ± 0.004)	330	13	500	R2 – Clock & Data Mgmt, Analog	9	14
PLCC-68	44	32.0 ± 0.1 (1.256 ± 0.004)	330	13	250	R2 – Clock & Data Mgmt, Analog	9	14
PLCC-84	44	36.0 ± 0.1 (1.418 ± 0.004)	330	13	250	R2 – Clock & Data Mgmt, Analog	9	14
PowerFLEX™	12	24.0 ± 0.1 (0.942 ± 0.004)	330	13	2,000	R7 – Analog	1	13
POWERMITE®	12	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, TR7 – Discrete	20	16
POWERMITE	12	4.0 ± 0.1 (0.157 ± 0.004)	330	13	12,000	T3, TR13 – Discrete	20	16
SC-59	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2 – Discrete	13	15
SC-59	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	13	15
SC-70	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	13	15
SC-70	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	13	15
SC-70 5 Lead	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Analog	15	15
SC-70 6 Lead	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Analog	22	17
SC-70 6 Lead	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Analog	22	17
SC-74	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	14	15
SC-74A	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	12	15
SC-75	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	13	15
SC-82	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	TR – Analog	10	15
SC-82AB	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Analog, Discrete	10	15
SC-88	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	22	17
SC-88	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2 – Discrete T1 – Analog	22	17
SC-88A	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2 – Discrete	15	15
SC-88A	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3, T4 – Discrete	15	15
SC-89	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	13	15
SC-89	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	13	15
SMA	12	4.0 ± 0.1 (0.157 ± 0.004)	178	7	1,500	T1 – Discrete	21	16
SMA	12	4.0 ± 0.1 (0.157 ± 0.004)	330	13	5,000	T3 – Discrete	21	16
SMB	12	8.0 ± 0.1 (0.315 ± 0.004)	178	7	1,000	T1 – Discrete	21	16
SMB	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	T3 – Discrete	21	16
SMC	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	T3 – Discrete	21	16
SO-8 (SOIC 8)	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500 / 3,000	R8 – Analog E.G.*	32	18
SO-8 (SOIC 8)	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500 / 3,000	R2 – TMOS, Analog, Clock & Data Mgmt	32	18
SO-8 (SOIC 8)	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500 / 3,000	T3 – EEPROM	32	18
SO-14 (SOIC 14)	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	3,000	R14 – Analog E.G.*	32	18
SO-14 (SOIC 14)	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	3,000	R2 – Clock & Data Mgmt, Logic, Analog	32	18
SO-16 (SOIC 16)	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	3,000	R2 – Clock & Data Mgmt, Logic, Analog	32	18

\* Applies to Analog devices manufactured at the East Greenwich, Rhode Island, USA facility.

## Embossed Tape and Reel Ordering Information

Package	Tape Width mm	Pitch mm (Dimension P <sub>1</sub> ) (inch)	Reel Size		Devices Per Reel and Min Order Quantity	Tape and Reel Suffix	Fig No	Page No
			(mm)	(in)				
SO-16 (SOIC 16)	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	3,000	R16 – Analog E.G.*	32	18
SO-16 Wide (SOIC 16W)	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	1,500	R2 – Clock & Data Mgmt, Logic, Analog	32	18
SO-16 Wide (SOIC 16W)	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	1,500	R16 – Analog E.G.*	32	18
SO-18 Wide (SOIC 18W)	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,000	R2 – Clock & Data Mgmt	32	18
SO-18 Wide (SOIC 18W)	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,000	R18 – Analog E.G.*	32	18
SO-20 Wide (SOIC 20W)	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,500	R2 – Analog, Clock & Data Mgmt	32	18
SO-20 Wide (SOIC 20W)	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,500	R20 – Analog E.G.*	32	18
SO-24 Wide (SOIC 24W)	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,500	R2 – Analog, Clock & Data Mgmt	32	18
SO-24 Wide (SOIC 24W)	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,500	R24 – Analog E.G.*	32	18
SO-28 Wide (SOIC 28W)	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,000	R2 – Analog, Clock & Data Mgmt	33	18
SO-28L Wide (SOIC 28W)	32	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,000	R3 – Analog	33	18
SO-28 Wide (SOIC 28W)	32	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,000	R28 – Analog E.G.*	33	18
SO-32 Wide (SOIC 32W)	32	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,000	R32 – Analog E.G.*	32	18
SOIC-EIAJ8	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	T2 – EEPROM	32	18
SOIC-EIAJ14	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	EL – Logic	32	18
SOIC-EIAJ16	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	EL – Logic	32	18
SOIC-EIAJ20	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	EL – Logic	32	18
SOD-123	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2 – Discrete	26	17
SOD-123	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	26	17
SOD-323	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	26	17
SOD-323	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	26	17
SOD-523	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	29	18
SOD-523	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	8,000	T5 – Discrete	29	18
SOD-723	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	8,000	T5 – Discrete	30	18
SOD-923	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	8,000	T5 – Discrete	30	18
SON-6	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Analog	27	17
SON-8	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Analog	N/A	N/A
SOP-16	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2 – Analog	32	18
SOT-143	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3, T4 – Discrete	25	17
SOT-143	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2, Discrete T – Analog	25	17
SOT-223	12	8.0 ± 0.1 (0.315 ± 0.004)	178	7	1,000	T1 – Discrete, Analog	31	18
SOT-223	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R3 or T3 – Analog E.G.*	31	18
SOT-223	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	4,000	T3 – Discrete, TMOS T3 – Analog	31	18
SOT-23	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, – Discrete TR, T1 – Analog	13	15
SOT-23	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	13	15

\* Applies to Analog devices manufactured at the East Greenwich, Rhode Island, USA facility.



## Embossed Tape and Reel Ordering Information

Package	Tape Width mm	Pitch mm (Dimension P <sub>1</sub> ) (inch)	Reel Size		Devices Per Reel and Min Order Quantity	Tape and Reel Suffix	Fig No	Page No
			(mm)	(in)				
SOT-23 5 Lead	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, TR, T – Analog	12	15
SOT-23 6 Lead	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, R1 – Analog	14	15
SOT-23L	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	4,000	R2 – Analog	13	15
SOT-323	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1 – Discrete	13	15
SOT-323	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	13	15
SOT-353	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2 – Discrete	15	15
SOT-353	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3, T4 – Discrete	15	15
SOT-553/563	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	4,000	T1 – Discrete, Logic	16,17	16
SOT-553/563	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	4,000	T2 – Discrete, Logic, Analog	16,17	16
SOT-553/563	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	8,000	T5 – Discrete, Logic	16,17	16
SOT-553/563	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	8,000	T6 – Discrete, Logic	16,17	16
SOT-723	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	8,000	T5 – Discrete	13	15
SOT-89	12	8.0 ± 0.1 (0.315 ± 0.004)	178	7	1,000	T1, R1 – Discrete T1 – Analog	23	17
SOT-883	8	2.0 ± 0.1 (0.158 ± 0.004)	178	7	8,000	T5 – Discrete	5	14
SOT-953/963	8	2.0 ± 0.05 (0.079 ± 0.002)	178	7	8,000	T5 – Discrete, Logic	18,19	16
SOT-1123	8	2.0 ± 0.1 (0.158 ± 0.004)	178	7	8,000	T5 – Discrete	28	17
SSOP-8	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	3,000	T1 – Analog	32	18
SSOP-14	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	R14 – Analog E.G.*	32	18
SSOP-16	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	R16 – Analog E.G.*	32	18
SSOP-20	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	R20 – Analog E.G.*	32	18
SSOP-24 Wide	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	R24 – Analog E.G.*	32	18
SSOP-36 EP	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,500	R2 – Analog	32	18
SSOP-36 EP	24*	12.0 ± 0.1 (0.471 ± 0.004)	330	13	1,500	R2 – Analog (*Non-standard)	32	18
TO-92	See TO-92 and other Axial Leaded package specifications beginning on page 27							
TQFP-32	16	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,000	R2 – Analog, Clock & Data Mgmt	8	14
TQFP-52	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	1,500	R2 – Clock & Data Mgmt	8	14
TQFP-64	24	16.0 ± 0.1 (0.630 ± 0.004)	330	13	1,500	R2 – Clock & Data Mgmt	8	14
TSOP-5	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2 – Discrete T1, T2, TR – Analog	12	15
TSOP-5	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Discrete	12	15
TSOP-6	8	4.0 ± 0.1 (0.157 ± 0.004)	178	7	3,000	T1, T2 – Analog, Discrete	14	15
TSOP-6	8	4.0 ± 0.1 (0.157 ± 0.004)	330	13	10,000	T3 – Analog, Discrete	14	15
TSSOP-10	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2 – Clock & Data Mgmt	32	18
TSSOP-14	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2 – Analog, Clock & Data Mgmt	32	18
TSSOP-16	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2 – Analog, Clock & Data Mgmt	32	18
TSSOP-20	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2 – Analog, Clock & Data Mgmt	32	18
TSSOP-24	16	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2 – Analog, Clock & Data Mgmt	32	18
TSSOP-48	24	12.0 ± 0.1 (0.471 ± 0.004)	330	13	2,500	R2 – Clock & Data Mgmt	32	18
TSSOP-8	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	2,500	R2 – Analog, Clock & Data Mgmt	32	18
TSSOP-8	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	4,000	R2 – Discrete, MOS	32	18
TSSOP-8	12	8.0 ± 0.1 (0.315 ± 0.004)	330	13	3,000	R3 – Discrete, MOS	32	18

US8	8	$4.0 \pm 0.1$ ( $0.157 \pm 0.004$ )	178	7	3,000	US – Logic	24	17
WLCSP $\leq$ 0.86x0.84mm	8	$2.0 \pm 0.1$ ( $0.079 \pm 0.004$ )	178	7	5000	TR	37–39	19,20
WLCSP $\leq$ 1.4x1.4mm	8	$2.0 \pm 0.1$ ( $0.079 \pm 0.004$ )	178	7	See Data Sheet	Various	37–39	19,20
WLCSP $\leq$ 3.3x3.3mm	8 8	$4.0 \pm 0.1$ ( $0.158 \pm 0.004$ ) $4.0 \pm 0.1$ ( $0.158 \pm 0.004$ )	178 330	7 13	See Data Sheet See Data Sheet	Various Various	37–39	19,20
WLCSP $>$ 3.3x3.3mm and $\leq$ 7x7mm	12 12	$8.0 \pm 0.1$ ( $0.315 \pm 0.004$ ) $8.0 \pm 0.1$ ( $0.315 \pm 0.004$ )	178 330	7 13	See Data Sheet See Data Sheet	Various Various	37–39	19,20
WLCSP $>$ 7x7mm and $\leq$ 8x8mm	12 12	$16.0 \pm 0.1$ ( $0.630 \pm 0.004$ ) $16.0 \pm 0.1$ ( $0.630 \pm 0.004$ )	178 330	7 13	See Data Sheet See Data Sheet	Various Various	37–39	19,20
WLCSP $>$ 8x8mm and $\leq$ 10.5x10.5mm	16 16	$12.0 \pm 0.1$ ( $0.471 \pm 0.004$ ) $12.0 \pm 0.1$ ( $0.471 \pm 0.004$ )	178 330	7 13	See Data Sheet See Data Sheet	Various Various	37–39	19,20
WLCSP >10.5x10.5mm	16 16	$16.0 \pm 0.1$ ( $0.630 \pm 0.004$ ) $16.0 \pm 0.1$ ( $0.630 \pm 0.004$ )	178 330	7 13	See Data Sheet See Data Sheet	Various Various	37–39	19,20
XLLGA	8	$2.0 \pm 0.1$ ( $0.158 \pm 0.004$ )	178	7	8,000	T5 – Discrete	35	19

\* Applies to Analog devices manufactured at the East Greenwich, Rhode Island, USA facility.

# Former CMD Tape & Reel Standards, by Package

Former CMD Tape and Reel Standards by Package

Package	Package Size (mm)	Tape Width	Reel Diameter	Quantity per Reel	P <sub>0</sub>	P <sub>1</sub>	Orientation Quadrant
CSP, 2-Bump	0.60 x 0.30 x 0.275	8 mm	178 mm (7")	15,000	4 mm	4 mm	Top
CSP, 4-Bump	0.8 x 0.8 x 0.50	8 mm	178 mm (7")	10,000	4 mm	2 mm	B
CSP, 4-Bump	0.8 x 0.8 x 0.60	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 4-Bump	0.96 x 0.96 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 4-Bump	0.96 x 0.96 x 0.65	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 5-Bump	1.05 x 0.76 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 5-Bump	1.20 x 0.80 x 0.60	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 5-Bump	1.33 x 0.96 x 0.606	8 mm	178 mm (7")	3500	4 mm	4 mm	A
CSP, 5-Bump	1.33 x 0.96 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	A
CSP, 5-Bump	1.41 x 0.93 x 0.606	8 mm	178 mm (7")	3500	4 mm	4 mm	A
CSP, 5-Bump	1.41 x 0.95 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	A
CSP, 5-Bump	1.59 x 1.22 x 0.64	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 6-Bump	1.46 x 0.96 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 6-Bump	1.72 x 1.22 x 0.64	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 6-Bump	1.804 x 1.154 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 8-Bump	1.16 x 1.16 x 0.60	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 8-Bump	1.20 x 1.20 x 0.60	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 8-Bump	1.43 x 1.41 x 0.605	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 8-Bump	1.60 x 1.60 x 0.65	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 9-bump	2.470 x 0.970 x 0.606	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 9-bump	2.470 x 0.970 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 10-Bump	1.56 x 1.053 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 10-Bump	1.67 x 1.11 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 10-Bump	1.67 x 1.14 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 10-Bump	1.96 x 1.33 x 0.606	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 10-Bump	1.96 x 1.33 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	A
CSP, 10-Bump	2.46 x 0.96 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 10-Bump	3.104 x 1.154 x 0.682	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 11-Bump	1.46 x 1.96 x 0.65	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 11-Bump	2.05 x 1.44 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 14-Bump	2.00 x 1.10 x 0.58	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	2.36 x 1.053 x 0.262	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	2.36 x 1.053 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	2.36 x 1.053 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	2.47 x 1.11 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	2.47 x 1.14 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	2.96 x 1.33 x 0.605	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	2.96 x 1.33 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B

For orientation and dimension standards, see diagrams on page 21.

**Former CMD Tape and Reel Standards by Package**

Package	Package Size (mm)	Tape Width	Reel Diameter	Quantity per Reel	P <sub>0</sub>	P <sub>1</sub>	Orientation Quadrant
CSP, 15-Bump	2.96 x 1.33 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	3.16 x 1.053 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	3.006 x 1.376 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 15-Bump	3.01 x 1.38 x 0.644	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 18-Bump	1.96 x 1.56 x 0.60	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 20-Bump	3.16 x 1.053 x 0.615	8 mm	178 mm (7")	3500	4 mm	4 mm	B
CSP, 20-Bump	3.27 x 1.11 x 0.615	12 mm	330 mm (13")	3500	4 mm	4 mm	B
CSP, 20-Bump	3.96 x 1.33 x 0.644	8 mm	178 mm (7")	3500	4 mm	8 mm	B
CSP, 20-Bump	3.96 x 1.586 x 0.640	12 mm	330 mm (13")	3500	4 mm	4 mm	B
CSP, 20-Bump	4.00 x 1.46 x 0.605	12 mm	330 mm (13")	3500	4 mm	4 mm	B
CSP, 20-Bump	4.00 x 1.46 x 0.606	12 mm	330 mm (13")	3500	4 mm	8 mm	B
CSP, 20-Bump	4.00 x 1.46 x 0.644	12 mm	330 mm (13")	3500	4 mm	8 mm	B
CSP, 20-Bump	4.006 x 1.376 x 0.644	12 mm	330 mm (13")	3500	4 mm	4 mm	B
CSP, 24-Bump	1.96 x 1.96 x 0.60	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 24-Bump	2.06 x 2.06 x 0.6	8 mm	178 mm (7")	5000	4 mm	4 mm	B
CSP, 24-Bump	2.60 x 2.60 x 0.65	8 mm	178 mm (7")	500	4 mm	4 mm	B
CSP, 25-Bump	2.00 x 2.00 x 0.60	8 mm	178 mm (7")	500	4 mm	4 mm	B
CSP, 49-Bump	2.80 x 2.80 x 0.50	8 mm	178 mm (7")	500	4 mm	4 mm	B
CSP, 49-Bump	2.80 x 2.80 x 0.60	8 mm	178 mm (7")	500	4 mm	4 mm	B
MSOP-8	3.00 x 3.00 x 0.85	12 mm	330 mm (13")	4000	4 mm	8 mm	A
MSOP-10	3.00 x 3.00 x 0.85	12 mm	330 mm (13")	4000	4 mm	8 mm	A
QSOP-16	4.90 x 3.89 x 1.55	12 mm	330 mm (13")	2500	4 mm	8 mm	A
QSOP-24	8.65 x 3.90 x 1.35	16 mm	178 mm (7")	1000	4 mm	8 mm	A
QSOP-24	8.65 x 3.90 x 1.35	16 mm	330 mm (13")	2500	4 mm	8 mm	A
SC70-3	2.05 x 1.25 x 0.95	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SC70-5	2.05 x 1.25 x 0.95	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SC70-5	2.05 x 1.25 x 0.95	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SC70-6	2.05 x 1.25 x 0.95	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SOD-882	1.00 x 0.60 x 0.50	8 mm	178 mm (7")	5000	4 mm	4 mm	A
SOIC-8	4.90 x 3.99 x 1.55	12 mm	330 mm (13")	2500	4 mm	8 mm	A
SOIC-8	4.90 x 6.00 x 1.55	12 mm	330 mm (13")	2500	4 mm	8 mm	A
SOT143	2.92 x 2.37 x 1.01	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SOT143-4	2.92 x 2.37 x 1.01	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SOT23-3	2.92 x 2.37 x 1.01	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SOT23-5	2.92 x 2.79 x 1.24	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SOT23-6	2.90 x 2.80 x 1.45	8 mm	178 mm (7")	3000	4 mm	4 mm	C
SOT-553	1.60 x 1.60 x 0.55	8 mm	178 mm (7")	5000	4 mm	4 mm	C
SOT-563	1.60 x 1.60 x 0.55	8 mm	178 mm (7")	5000	4 mm	4 mm	C
SOT-593	1.00 x 0.80 x 0.45	8 mm	178 mm (7")	8000	4 mm	4 mm	B
CUDFN-6	1.60 x 1.60 x 0.60	8 mm	178 mm (7")	2500	4 mm	4 mm	A

For orientation and dimension standards, see diagrams on page 21.

**Former CMD Tape and Reel Standards by Package**

Package	Package Size (mm)	Tape Width	Reel Diameter	Quantity per Reel	P <sub>0</sub>	P <sub>1</sub>	Orientation Quadrant
CUDFN-6	2.00 x 2.00 x 0.65	8 mm	178 mm (7")	2500	4 mm	4 mm	A
TDFN-8	1.70 x 1.35 x 0.75	8 mm	178 mm (7")	3000	4 mm	4 mm	A
TDFN-8	2.00 x 2.00 x 0.75	8 mm	178 mm (7")	3000	4 mm	4 mm	A
TDFN-8	3.00 x 3.00 x .075	12 mm	330 mm (13")	3000	4 mm	8 mm	A
TDFN-12	3.00 x 1.35 x 0.75	8 mm	178 mm (7")	3000	4 mm	4 mm	A
TDFN-16	4.00 x 1.60 x 0.75	12 mm	178 mm (7")	3000	4 mm	4 mm	A
TDFN-16	4.00 x 1.70 x 0.75	12 mm	330 mm (13")	3000	4 mm	8 mm	A
TDFN-16	6.00 x 4.00 x 0.75	12 mm	330 mm (13")	3000	4 mm	8 mm	A
TSSOP-8	3.00 x 6.38 x 1.10	12 mm	330 mm (13")	2500	4 mm	8 mm	A
TSSOP-38	9.70 x 6.40 x 1.20	16 mm	330 mm (13")	2500	4 mm	12 mm	A
UDFN-6	1.25 x 1.0 x 0.50	8 mm	178 mm (7")	3000	4 mm	4 mm	A
UDFN-8	1.70 x 1.35 x 0.50	8 mm	178 mm (7")	3000	4 mm	4 mm	A
UDFN-8	1.70 x 1.35 x 0.50	8 mm	178 mm (7")	3000	4 mm	4 mm	A
UDFN-8	2.00 x 2.00 x 0.55	8 mm	178 mm (7")	3000	4 mm	4 mm	A
UDFN-12	2.50 x 1.20 x 0.50	8 mm	178 mm (7")	3000	4 mm	4 mm	A
UDFN-12	2.50 x 1.35 x 0.50	8 mm	178 mm (7")	3000	4 mm	4 mm	A
UDFN-16	3.30 x 1.35 x 0.50	8 mm	178 mm (7")	3000	4 mm	4 mm	A
uUDFN-10	2.50 x 1.00 x 0.50	8 mm	178 mm (7")	3000	4 mm	4 mm	A
X3DFN	0.62 x 0.62 x 0.32	8 mm	178 mm (7")	15,000	2 mm	2 mm	Top

For orientation and dimension standards, see diagrams on page 21.


# Product Orientation

Direction of Feed



**Figure 1. D<sup>2</sup>PAK**

24 mm (Tape Width, Typical)




5 Lead – T4 Discrete  
R4, R5 Analog

7 Lead – R7 Analog  
PowerFLEX-7 – R7 Analog

3 Lead – T4 Discrete  
R3, R4 Analog

**Figure 2. DPAK**


16 mm



Discrete Suffix – T4  
Analog Suffix – R or RK

**Figure 3. DPAK**


16 mm



Discrete, Analog  
Suffix – T5

**Figure 4. DPAK**

16 mm



Discrete Suffix – RL

## Product Orientation (continued)

Direction of Feed



Figure 5. SOT-883




Figure 6. DSN




Figure 7. 6-Bump, 9-Bump, 10-Bump  
Flip-Chip/DCA




Figure 8. LQFP, TQFP





Figure 9. PLCC




## Product Orientation (continued)

Direction of Feed




**Figure 10. SC82 / SC82-AB**  
"TR" Suffix – Option 1, 3




"T1" Pin One Opposing Sprocket Hole (3k Reel)  
"T3" Pin One Opposing Sprocket Hole (10k Reel)

**Figure 11. ChipFET (8-Lead)**  
"T1" Suffix – Option 1




"T1" Pin One Opposing Sprocket Hole (3k Reel)

**Figure 12. TSOP-5 / SOT23-5 / SC-74A**  
"T" or "TR" Suffix – Option 1, 3




"T1" Pin One Opposing Sprocket Hole (3k Reel)  
"T3" Pin One Opposing Sprocket Hole (10k Reel)

Option 2




"T2" Pin One Toward Sprocket Hole (3k Reel)

**Figure 13. SOT-23 / SOT-23L / SOT-323 / SOT-723 / SC-59 / SC-70 / SC-75 / SC-89**  
"T5", "TR" or "R2" Suffix – Option 1, 3




"T1" Single Lead Toward Sprocket Hole (3k Reel)  
"T5" Single Lead Toward Sprocket Hole (8k Reel)  
"T3" Single Lead Toward Sprocket Hole (10k Reel)

Option 2




"T2" Single Lead Opposing Sprocket Hole (3k Reel)  
(This Orientation Applies to SC-59 Only)

**Figure 14. TSOP-6 / SOT23-6 / SC-74**  
"T" or "TR" Suffix – Option 1, 3




"T1" Pin One Opposing Sprocket Hole (3k Reel)  
"T3" Pin One Opposing Sprocket Hole (10k Reel)

Option 2




"T2" Pin One Toward Sprocket Hole (3k Reel)

**Figure 15. SC-88A / SC70-5 / SOT-353**  
Option 1, 3



"T1" Pin One Toward Sprocket Hole (3k Reel)  
"T3" Pin One Toward Sprocket Hole (10k Reel)

Option 2, 4



"T2" Pin One Opposing Sprocket Hole (3k Reel)  
"T4" Pin One Opposing Sprocket Hole (10k Reel)




## Product Orientation (continued)

Direction of Feed




**Figure 16. SOT-553**

Option 1




"T1" Pin One Toward Sprocket Hole (4k Reel)

Option 2




"T2" Pin One Opposing Sprocket Hole (4k Reel)

Option 5



"T5" Pin One Toward Sprocket Hole (8k Reel)


Option 6



"T6" Pin One Opposing Sprocket Hole (8k Reel)

**Figure 18. SOT-953**


Option 5



"T5" Pin One Toward Sprocket Hole (8k Reel)


**Figure 20. POWERMITE®**

"T1" Suffix – Option 1




**Figure 17. SOT-563**

Option 1




"T1" Pin One Toward Sprocket Hole (4k Reel)

Option 2




"T2" Pin One Opposing Sprocket Hole (4k Reel)

Option 5



"T5" Pin One Toward Sprocket Hole (8k Reel)


Option 6



"T6" Pin One Opposing Sprocket Hole (8k Reel)

**Figure 19. SOT-963**


Option 5



"T5" Pin One Toward Sprocket Hole (8k Reel)

**Figure 21. SMA, SMB, SMC**

"TR" or "R2" Suffix – Option 1, 3



### Unidirectional

**SMA:** "T1" Cathode Toward Sprocket Hole (1.5k Reel)

"T3" Cathode Toward Sprocket Hole (5k Reel)

**SMB/SMC:** "T1" Cathode Toward Sprocket Hole (1k Reel)

"T3" Cathode Toward Sprocket Hole (2.5k Reel)

### Bidirectional


Same as above except no orientation

## Product Orientation (continued)

Direction of Feed




**Figure 22. SC-88 / SC70-6 / SOT-363**  
Option 1, 3




"T1" Pin One Toward Sprocket Hole (3k Reel)  
"T3" Pin One Toward Sprocket Hole (10k Reel)

Option 2



"T2" Pin One Opposing Sprocket Hole (3k Reel)


**Figure 24. ULTRA SMALL 8**



Pin One Opposing Sprocket Hole (3k Reel)


**Figure 25. SOT-143**

"T" or "TR" Suffix - Option 1, 3




"T1" Wide Lead Tape Opposing Sprocket Hole (3k Reel)  
"T3" Wide Lead Tape Opposing Sprocket Hole (10k Reel)

Option 2, 4




"T2" Wide Lead Tape Toward Sprocket Hole (3k Reel)  
"T4" Wide Lead Tape Toward Sprocket Hole (10k Reel)

**Figure 27. SON-6**




**Figure 23. SOT-89**  
"R1" Suffix




"R1" Pin One Opposing Sprocket Hole (1k Reel)

"T1" Suffix



"T1" Single Lead Toward Sprocket Hole (1k Reel)


"T2" Suffix



"T2" Single Lead Opposing Sprocket Hole (1k Reel)


**Figure 26. SOD-123 / SOD-323**

Option 1, 3




"T1" Cathode Lead Toward Sprocket Hole (3k Reel)  
"T3" Cathode Lead Toward Sprocket Hole (10k Reel)

Option 2



"T2" Cathode Lead Opposing Sprocket Hole (3k Reel)

**Figure 28. SOT-1123**



"T5" Single Lead Toward Sprocket Hole (8k Reel)


## Product Orientation (continued)

Direction of Feed




**Figure 29. SOD-523**

Option 1



"T1" Cathode Lead Toward Sprocket Hole (3k Reel)


Option 5



"T5" Cathode Lead Toward Sprocket Hole (8k Reel)


**Figure 30. SOD-723, SOD-923**

Option 5



"T5" Cathode Lead Toward Sprocket Hole (8k Reel)

**Figure 31. SOT-223**




"T1" Single Lead Toward Sprocket Hole (1k Reel)

"T3" Single Lead Toward Sprocket Hole (4k Reel)

"R3" Single Lead Toward Sprocket Hole (2.5k Reel)

**Figure 32. Micro8™ / Micro10 / SO / SOIC / SOIC-EIAJ / SOP / SSOP / TSSOP**




Pin 1 (Upper Left)

EL – Logic  
R2 – Clock & Data Mgt.  
R or R2 – Analog  
T2 or T3 – EEPROM

**Figure 33. SO-28W**

32 mm



R3 – Analog


## Product Orientation (continued)

Direction of Feed




Leadless Packages

Figure 34. X3DFN




T5 – Cathode Band Toward Sprocket Hole (15k Reel)

Figure 35. XLLGA



T5 – Pin One Opposing Sprocket Hole (8k Reel)


Figure 36. FCBGA (BGA)



TA, TW


Pin 1 (Upper Left)  
(On circular sprocket hole side of the tape)

Figure 37. DFN/QFN/WLCSP-5



TA, TW, TR

Figure 38. DFN/QFN (LPCC)/WLCSP-4



TB, TX, TR

Pin 1  
(Upper Right)

Package	Pre Jan 2007	Post Jan 2007
DFN / QFN Square (LPCC)	T1	TB, TX
	T4	TB, TX
	R2	TB, TX
DFN / QFN Rectangular (LPCC)	T1	TA, TW
	R2	TA, TW
DFN / QFN	T2	TA, TW
	R2	TA, TW
FCBGA / BGA	R2	TA, TW
WLCSP	–	TR

# Leadless Package Pin 1 Orientation for Tape and Reel (QFN, DFN, FCBGA, BGA, LPCC)





Figure 39. Leadless Package Pin 1 Orientation for Tape and Reel (Effective January 2007)


Part Number Suffix				
Shipping Type*	Pin1 Location	Blank or Pb-Free	Remark:	Reel Size (mm) diameter
T	A	G	Quadrant 1--upper left	177
T	B	G	Quadrant 2--upper right	178
T	C	G	Quadrant 3--lower left	178
T	D	G	Quadrant 4--lower right	178
T	W	G	Quadrant 1--upper left	330
T	X	G	Quadrant 2--upper right	330
T	Y	G	Quadrant 3--lower left	330
T	Z	G	Quadrant 4--lower right	330
T	N	G	North (upper center)	178
T	S	G	South (lower center)	178
T	T	G	Top (upper center)	330
T	U	G	Under (lower center)	330
T	L	G	Left center	178
T	R	G	Right center	178
T	E	G	Left center	330
T	F	G	Right center	330

\*T = Tape

# Tape and Reel Dimensions and Orientation for Former CMD Devices



# Embossed Tape and Reel Data Carrier Tape Standards



## DIMENSIONS

Tape Size (W)	$B_1$ Max (Note 1)	D	$D_1$	E	F	K	$P_0$	$P_2$	R Min	T Max	W Max
8 mm	4.55 mm (0.179")	$1.5 \pm 0.1 \text{ mm}$ (0.059 + 0.004" - 0.0)	1.0 Min (0.039") or 0.5 mm Min (0.020") or 0.2 mm Min (0.008")	$1.75 \pm 0.1 \text{ mm}$ (0.069 ± 0.004")	$3.5 \pm 0.05 \text{ mm}$ (0.138 ± 0.002")	2.4 mm Max (0.094")	$4.0 \pm 0.1 \text{ mm}$ (0.157 ± 0.004")	$2.0 \pm 0.1 \text{ mm}$ (0.079 ± 0.002")	25 mm (0.98")	0.6 mm (0.024")	8.3 mm (0.327")
12 mm	8.2 mm (0.323")		1.5 mm Min (0.060")		$5.5 \pm 0.05 \text{ mm}$ (0.217 ± 0.002")	6.4 mm Max (0.252")			30 mm (1.18")		$12 \pm 0.30 \text{ mm}$ (0.470 ± 0.012")
16 mm	12.1 mm (0.476")				$7.5 \pm 0.10 \text{ mm}$ (0.295 ± 0.004")	7.9 mm Max (0.311")					16.3 mm (0.642")
24 mm	20.1 mm (0.791")				$11.5 \pm 0.1 \text{ mm}$ (0.453 ± 0.004")	11.9 mm Max (0.468")					24.3 mm (0.957")

Metric dimensions govern – English are in parentheses for reference only.



- Pitch information (dimension  $P_1$ ) is contained in the embossed tape and reel ordering information beginning on Page 5.
- $A_0$ ,  $B_0$ , and  $K_0$  are determined by component size. The clearance between the components and the cavity must be within 0.05 mm min to 0.50 mm max. The component cannot rotate more than 10° within the determined cavity.

# Tape Ends for Finished Goods

## Leader and Trailer


The TRAILER is a minimum of 160 mm in length and it consists of empty cavities with sealed cover tape.

The LEADER is a minimum of 400 mm in length and it consists of empty cavities with sealed cover tape.





# Reel Dimensions



Reel Diameter	Tape Size	A mm (inches)		B mm (inches)		C mm (inches)		D (Max)	E (Max)
		Min	Max	Min	Max	Min	Max		
178.0 (7.01)	16.0 (0.63)		50.0 (1.97)	6.5 (0.26)	7.5 (0.30)	16.4 (0.65)	18.4 (0.72)	22.4 (0.88)	19.4 (0.76)
330.0 (12.99)	12.0 (0.47)	178.0 (7.01)		4.5 (0.18)	5.5 (0.22)	12.4 (0.49)	14.4 (0.57)	18.4 (0.72)	15.4 (0.61)
330.0 (12.99)	56.0 (2.20)	150.0 (5.91)		10.0 (0.39)	11.0 (0.43)	56.4 (2.22)	58.4 (2.30)	62.4 (2.46)	59.4 (2.34)
330.0 (12.99)	44.0 (1.73)	100.0 (3.94)		10.0 (0.39)	11.0 (0.43)	44.4 (1.75)	46.4 (1.83)	62.4 (2.46)	47.4 (1.87)
330.0 (12.99)	32.0 (1.26)	100.0 (3.94)		10.0 (0.39)	11.0 (0.43)	32.4 (1.28)	34.4 (1.35)	38.4 (1.51)	35.4 (1.39)
330.0 (12.99)	24.0 (0.94)	60.0 (2.36)		9.5 (0.37)	10.5 (0.41)	24.4 (0.96)	26.4 (1.04)	30.4 (1.51)	27.4 (1.08)
330.0 (12.99)	16.0 (0.63)			6.5 (0.26)	7.5 (0.30)	16.4 (0.65)	18.4 (0.72)	22.4 (0.88)	19.4 (0.76)
330.0 (12.99)	12.0 (0.47)			4.5 (0.18)	5.5 (0.22)	12.4 (0.49)	14.4 (0.57)	18.4 (0.72)	15.4 (0.61)
330.0 (12.99)	8.0 (0.31)	50.0 (1.97)		2.5 (0.10)	3.5 (0.14)	8.4 (0.33)	9.9 (0.39)	14.4 (0.57)	10.9 (0.43)
178.0 (7.01)	12.0 (0.47)	50.0 (1.97)		4.5 (0.18)	5.5 (0.22)	12.4 (0.49)	14.4 (0.57)	18.4 (0.72)	15.4 (0.61)
178.0 (7.00)	8.0 (0.31)	50.0 (1.97)		2.5 (0.10)	3.5 (0.14)	8.4 (0.33)	9.9 (0.39)	14.4 (0.47)	10.9 (0.43)
330.0 (12.99)	8.0 (0.31)	50.0 (1.97)		4.0 (0.16)	5.0 (0.20)	8.4 (0.33)	9.9 (0.39)	14.4 (0.57)	10.9 (0.43)
178.0 (7.00)	8.0 (0.31)	50.0 (1.97)		4.0 (0.16)	5.0 (0.20)	8.4 (0.33)	9.9 (0.39)	14.4 (0.57)	10.9 (0.43)

## Reel Dimensions (continued)




Figure 40. Front View of 178 mm (7.0 in) Reel




Figure 41. Front View of 330 mm (12.99 in) Reel

### NOTES:

#### 1. LABEL PLACEMENT AREA:

- All reels must have flat area on the front flange of the reel that will fit two 41.3 mm (1.65 in) by 125 mm (4.90 in) ON Semiconductor barcode labels.
- If there are any flange openings on the front side of the 178 mm (7.00 in) reel they must be designed in locations so that two of the 41.3 mm (1.65 in) ON Semiconductor barcode labels can be applied parallel to each other as in Figure 40.
- If there are any flange opening on the front flange of the 330 mm (13.0 in) reel they must be designed in locations so that two of the 41.3 mm (1.65 in) by 125 mm (4.90 in) ON Semiconductor barcode labels can be applied parallel to each other as in Figure 41.

#### 2. FLANGE OPENINGS


- Flange opening on the front and the back of the reel are a supplier option but must meet all of the requirements in Note 1. The preferred size for the 176 mm (7.0 in) reel is shown in Figure 40.
- The tape loading opening must be as in Detail A.

#### 3. GRAPHICS:


- The letters MPN and CPN are a option. The size and thickness of the letters are the manufacturer's option and are not to be used for inspection criteria.
- The embossed lines on the reel are a option. If the lines are used they must be located as in Figure 40 and 41. They must be a minimum 38 mm (1.50 in) long. The thickness is a manufacturer's option and not to be used for inspection criteria.

# Reel Labeling

Place the reel on an ESD protective surface so that the round sprocket holes are on the bottom. The direction of travel when unwound should be from the top right quadrant. See illustration below.



**Figure 42. Round and Oval Sprocket Holes Used with 32 mm, 42 mm, 44 mm and 52 mm Tape (holes on both sides)**



**Figure 43. Round Sprocket Holes Used with 8 mm, 12 mm, 16 mm and 24 mm Tape (holes on one side only)**


# TO-92 EIA, IEC, EIAJ

## Radial Tape in Fan Fold Box or On Reel

Radial tape in fan fold box or on reel of the reliable TO-92 package are the best methods of capturing devices for automatic insertion in printed circuit boards. These methods of taping are compatible with various equipment for active and passive component insertion.

- Available in Fan Fold Box
- Available on 365 mm Reels
- Accommodates All Standard Inserters
- Allows Flexible Circuit Board Layout
- 2.5 mm Pin Spacing for Soldering
- EIA-468, IEC 286-2, EIAJ RC1008B

### TO-92 RADIAL TAPE IN FAN FOLD BOX OR ON REEL



#### Ordering Notes:

When ordering radial tape in fan fold box or on reel, specify the style per Figures 45, 46, 52 and 53. Add the suffix “RLR” and “Style” to the device title, i.e. 2N5060RLRA. This will be a standard 2N5060 radial taped and supplied on a reel. Some products only utilize the last 2 digits. Please refer to the ON Semiconductor device data sheet for exact ordering information.

- Fan Fold Box Information – Minimum order quantity 1 Box. Order in increments of 2000.
- Reel Information – Minimum order quantity 1 Reel. Order in increments of 2000.

#### US/EUROPEAN SUFFIX CONVERSIONS

U.S.	Europe	Package Style
RLRA, RA	RL	Reel
RLRE, RE	RL1	Reel
RLRM, RM	ZL1	Fan Fold
RLRP, RP	–	Fan Fold

# TO-92 EIA RADIAL TAPE IN FAN FOLD BOX OR ON REEL





Figure 44. Device Positioning on Tape

Symbol	Item	Specification			
		Inches		Millimeter	
		Min	Max	Min	Max
D	Tape Feedhole Diameter	0.1496	0.1653	3.8	4.2
D2	Component Lead Thickness Dimension	0.015	0.020	0.38	0.51
F1, F2	Component Lead Pitch	0.0945	0.110	2.4	2.8
H	Bottom of Component to Seating Plane	0.059	0.156	1.5	4.0
H1	Feedhole Location	0.3346	0.3741	8.5	9.5
H2A	Deflection Left or Right	0	0.039	0	1.0
H2B	Deflection Front or Rear	0	0.051	0	1.0
H4	Feedhole to Bottom of Component	0.7086	0.768	18	19.5
H5	Feedhole to Seating Plane	0.610	0.649	15.5	16.5
L	Defective Unit Clipped Dimension	0.3346	0.433	8.5	11
L1	Lead Wire Enclosure	0.09842	–	2.5	–
P	Feedhole Pitch	0.4921	0.5079	12.5	12.9
P1	Feedhole Center to Center Lead	0.2342	0.2658	5.95	6.75
P2	First Lead Spacing Dimension	0.1397	0.1556	3.55	3.95
T	Adhesive Tape Thickness	0.06	0.08	0.15	0.20
T1	Overall Taped Package Thickness	–	0.0567	–	1.44
T2	Carrier Strip Thickness	0.014	0.027	0.35	0.65
W	Carrier Strip Width	0.6889	0.7481	17.5	19
W1	Adhesive Tape Width	0.2165	0.2841	5.5	6.3
W2	Adhesive Tape Position	0.0059	0.01968	0.15	0.5

- Maximum alignment deviation between leads not to be greater than 0.2 mm.
- Defective components shall be clipped from the carrier tape such that the remaining protrusion (L) does not exceed a maximum of 11 mm.
- Component lead to tape adhesion must meet the pull test requirements established in Figures 48, 49 and 50.
- Maximum non-cumulative variation between tape feed holes shall not exceed 1 mm in 20 pitches.
- Hold down tape not to extend beyond the edge(s) of carrier tape and there shall be no exposure of adhesive.
- No more than 1 consecutive missing component is permitted.
- A tape trailer and leader, having at least three feed holes is required before the first and after the last component.
- Splices will not interfere with the sprocket feed holes.


# TO-92 EIA RADIAL TAPE IN FAN FOLD BOX OR ON REEL

## FAN FOLD BOX STYLES




Style M fan fold box is equivalent to styles E and F of reel pack dependent on feed orientation from box.

**Figure 45. Style RLRM, RM**




Style P fan fold box is equivalent to styles A and B of reel pack dependent on feed orientation from box.

**Figure 46. Style RL RP, RP**




**Figure 47. Fan Fold Box Dimensions**

## ADHESION PULL TESTS




The component shall not pull free with a 300 gram load applied to the leads for  $3 \pm 1$  second.

**Figure 48. Test #1**



The component shall not pull free with a 70 gram load applied to the leads for  $3 \pm 1$  second.


**Figure 49. Test #2**



There shall be no deviation in the leads and no component leads shall be pulled free of the tape with a 500 gram load applied to the component body for  $3 \pm 1$  second.


**Figure 50. Test #3**

# TO-92 EIA RADIAL TAPE IN FAN FOLD BOX OR ON REEL: REEL STYLES




Material used must not cause deterioration of components or degrade lead solderability

**Figure 51. Reel Specifications**



**Figure 52. Style RLRA, RA**



**Figure 53. Style RLRE, RE**

# Lead Tape Packaging Standards for Axial-Lead Components

## 1.0 SCOPE

This section covers packaging requirements for the following axial-lead component's use in automatic testing and assembly equipment: ON Semiconductor Case 17-02, Case 41A-02, Case 51-02 (DO-7), Case 59-03 (DO-41), Case 59-04, Case 194-04 and Case 299-02 (DO-35). Packaging, as covered in this section, shall consist of axial-lead components mounted by their leads on pressure sensitive tape, wound onto a reel.

## 2.0 PURPOSE

This section establishes ON Semiconductor standard practices for lead-tape packaging of axial-lead components and meets the requirements of EIA Standard RS-296-D "Lead-taping of Components on Axial Lead Configuration for Automatic Insertion," level 1.

## 3.0 REQUIREMENTS

### 3.1 Component Leads

**3.1.1** – Component leads shall not be bent beyond dimension E from their normal position. See Figure 55.

**3.1.2** – The "C" dimension shall be governed by the overall length of the reel packaged component. The distance between flanges shall be 0.059 inch to 0.315 inch greater than the overall component length. See Figures 55 and 56.

**3.1.3** – Cumulative dimension "A" tolerance shall not exceed 0.059 over 6 in consecutive components.

### 3.2 Orientation

All polarized components must be oriented in one direction. The cathode lead tape shall be any color except white and the anode tape shall be white. See Figure 54.

### 3.3 Reeling

**3.3.1** – Components on any reel shall not represent more than two date codes when date code identification is required.

**3.3.2** – Component's leads shall be positioned perpendicularly between pairs of 0.250 inch tape. See Figure 55.

**3.3.3** – A minimum 12 inch leader of tape shall be provided before the first and last component on the reel.

**3.3.4** – 50 lb. Kraft paper is wound between layers of components as far as necessary for component protection.

**3.3.5** – Components shall be centered between tapes such that the difference between D1 and D2 does not exceed 0.055.

**3.3.6** – Staples shall not be used for splicing. No more than four layers of tape shall be used in any splice area and no tape shall be offset from another by more than 0.031 inch noncumulative. Tape splices shall overlap at least 6 inches for butt joints and at least 3 inches for lap joints and shall not be weaker than unspliced tape.

**3.3.7** – Quantity per reel shall be as indicated in Table 1. Orders for tape and reeled product will only be processed and shipped in full reel increments. Scheduled orders must be in releases of full reel increments or multiples thereof.

**3.3.8** – A maximum of 0.25% of the components per reel quantity may be missing without consecutive missing per level 1 of RS-296-D.

**3.3.9** – The single face roll pad shall be placed around the finished reel and taped securely. Each reel shall then be placed in an appropriate container.

## 3.4 Marking

Minimum reel and carton marking shall consist of the following (see Figure 56):

ON Semiconductor part number

Quantity

Manufacturer's name

Date codes (when applicable; see note 3.3.1)

## 4.0

Requirements differing from this ON Semiconductor standard shall be negotiated with the factory.


The packages indicated in the following table are suitable for lead tape packaging. Table 1 indicates the specific devices (transient voltage suppressors and/or Zeners) that can be obtained from ON Semiconductor in reel packaging and provides the appropriate packaging specification.




# Lead Tape Packaging Standards for Axial-Lead Components

**Table 1. PACKAGING DETAILS** (all dimensions in inches)


Case Type	Product Category	Device Title Suffix	MPQ Quantity Per Reel	Component Spacing A Dimension	Tape Spacing B Dimension	Reel Dimension C	Reel Dimension D (Max)	Max Off Alignment E
Case 17	Surmetic 40 & 600 Watt TVS	RL	4000	$0.2 \pm 0.015$	$2.062 \pm 0.059$	3	14	0.047
Case 41A	1500 Watt TVS	RL4	1500	$0.4 \pm 0.02$	$2.062 \pm 0.059$	3	14	0.047
Case 59	DO-41 Glass & DO-41 Surmetic 30	RL	6000	$0.2 \pm 0.015$	$2.062 \pm 0.059$	3	14	0.047
	Rectifier							
Case 59	500 Watt TVS	RL	500	$0.2 \pm 0.02$	$2.062 \pm 0.059$	3	14	0.047
	Rectifier							
Case 194	110 Amp TVS (Automotive)	RL	800	$0.4 \pm 0.02$	$1.875 \pm 0.059$	3	14	0.047
	Rectifier							
Case 267	Rectifier	RL	1500	$0.4 \pm 0.02$	$2.062 \pm 0.059$	3	14	0.047
Case 299	DO-35 Glass	RL	5000	$0.2 \pm 0.02$	$2.062 \pm 0.059$	3	14	0.047
Case 267	Schottky & Ultrafast Rectifiers	RL	1500	$0.4 \pm 0.02$	$2.062 \pm 0.059$	3	14	0.047
Case 267	Fast Recovery & General Purpose Rectifiers	RL	1200	$0.4 \pm 0.02$	$2.062 \pm 0.059$	3	14	0.047



**Figure 54. Reel Packing**



**Figure 55. Component Spacing**



**Figure 56. Reel Dimensions** (Item references appear on Page 31)

## INFORMATION FOR USING SURFACE MOUNT PACKAGES

### RECOMMENDED FOOTPRINTS FOR SURFACE MOUNTED APPLICATIONS

Surface mount board layout is a critical portion of the total design. The footprint for the semiconductor packages must be the correct size to ensure proper solder connection

interface between the board and the package. With the correct pad geometry, the packages will self align when subjected to a solder reflow process.

### POWER DISSIPATION FOR A SURFACE MOUNT DEVICE

The power dissipation for a surface mount device is a function of the drain/collector pad size. These can vary from the minimum pad size for soldering to a pad size given for maximum power dissipation. Power dissipation for a surface mount device is determined by  $T_{J(max)}$ , the maximum rated junction temperature of the die,  $R_{\theta JA}$ , the thermal resistance from the device junction to ambient, and the operating ambient temperature,  $T_A$ . Using the values provided on the data sheet,  $P_D$  can be calculated as follows:

$$P_D = \frac{T_{J(max)} - T_A}{R_{\theta JA}}$$

The values for the equation are found in the maximum ratings table on the data sheet. Substituting these values into the equation for an ambient temperature  $T_A$  of 25°C, one can calculate the power dissipation of the device. For example, for a SOT-223 device,  $P_D$  is calculated as follows.

$$P_D = \frac{150^\circ\text{C} - 25^\circ\text{C}}{156^\circ\text{C/W}} = 800 \text{ milliwatts}$$

The 156°C/W for the SOT-223 package assumes the use of the recommended footprint on a glass epoxy printed circuit board to achieve a power dissipation of 800 milliwatts. There are other alternatives to achieving higher power dissipation from the surface mount packages. One is to increase the area of the drain/collector pad. By increasing the area of the drain/collector pad, the power dissipation can be increased. Although the power dissipation can almost be doubled with this method, area is taken up on the printed circuit board which can defeat the purpose of using surface mount technology. For example, a graph of  $R_{\theta JA}$  versus drain pad area is shown in Figures 57, 58 and 59.

Another alternative would be to use a ceramic substrate or an aluminum core board such as Thermal Clad™. Using a board material such as Thermal Clad, an aluminum core board, the power dissipation can be doubled using the same footprint.




Figure 57. Thermal Resistance versus Drain Pad Area for the SOT-223 Package (Typical)




Figure 58. Thermal Resistance versus Drain Pad Area for the DPAK Package (Typical)





Figure 59. Thermal Resistance versus Drain Pad Area for the D<sup>2</sup>PAK Package (Typical)

## SOLDER STENCIL GUIDELINES

Prior to placing surface mount components onto a printed circuit board, solder paste must be applied to the pads. Solder stencils are used to screen the optimum amount. These stencils are typically 0.008 inches thick and may be made of brass or stainless steel. For packages such as the SC-59, SC-70/SOT-323, SOD-123, SOT-23, SOT-143, SOT-223, SO-8, SO-14, SO-16, and SMB/SMC diode packages, the stencil opening should be the same as the pad size or a 1:1 registration. This is not the case with the DPAK and D<sup>2</sup>PAK packages. If a 1:1 opening is used to screen solder onto the drain pad, misalignment and/or “tombstoning” may occur due to an excess of solder. For these two packages, the opening in the stencil for the paste should be approximately 50% of the tab area. The opening for the leads is still a 1:1 registration. Figure 60 shows a typical stencil for the DPAK and D<sup>2</sup>PAK packages. The

pattern of the opening in the stencil for the drain pad is not critical as long as it allows approximately 50% of the pad to be covered with paste.



**Figure 60. Typical Stencil for DPAK and D<sup>2</sup>PAK Packages**

## SOLDERING PRECAUTIONS

The melting temperature of solder is higher than the rated temperature of the device. When the entire device is heated to a high temperature, failure to complete soldering within a short time could result in device failure. Therefore, the following items should always be observed in order to minimize the thermal stress to which the devices are subjected.

- Always preheat the device.
- The delta temperature between the preheat and soldering should be 100°C or less.\*
- When preheating and soldering, the temperature of the leads and the case must not exceed the maximum temperature ratings as shown on the data sheet. When using infrared heating with the reflow soldering method, the difference should be a maximum of 10°C.
- For wave soldering, the soldering temperature and time should not exceed 260°C for more than 10 seconds. For other reflow methods such as convection and IR ovens, refer to the reflow profiles on the following pages.

- When shifting from preheating to soldering, the maximum temperature gradient shall be 5°C or less.
- After soldering has been completed, the device should be allowed to cool naturally for at least three minutes. Gradual cooling should be used since the use of forced cooling will increase the temperature gradient and will result in latent failure due to mechanical stress.
- Mechanical stress or shock should not be applied during cooling.

\* Soldering a device without preheating can cause excessive thermal shock and stress which can result in damage to the device.

\* Due to shadowing and the inability to set the wave height to incorporate other surface mount components, the D<sup>2</sup>PAK is not recommended for wave soldering.

## TYPICAL SOLDER HEATING PROFILE

For any given circuit board, there will be a group of control settings that will give the desired heat pattern. The operator must set temperatures for several heating zones and a figure for belt speed. Taken together, these control settings make up a heating “profile” for that particular circuit board. On machines controlled by a computer, the computer remembers these profiles from one operating session to the next. Figure 61 shows a typical heating profile for use when soldering a surface mount device to a printed circuit board. This profile will vary among soldering systems, but it is a good starting point. Factors that can affect the profile include the type of soldering system in use, density and types of components on the board, type of solder used, and the type of board or substrate material being used. This profile shows temperature versus time. The line on the graph shows the

actual temperature that might be experienced on the surface of a test board at or near a central solder joint. The two profiles are based on a high density and a low density board. The Vitronics SMD310 convection/infrared reflow soldering system was used to generate this profile. The type of solder used was 62/36/2 Tin Lead Silver with a melting point between 177–189°C. When this type of furnace is used for solder reflow work, the circuit boards and solder joints tend to heat first. The components on the board are then heated by conduction. The circuit board, because it has a large surface area, absorbs the thermal energy more efficiently, then distributes this energy to the components. Because of this effect, the main body of a component may be up to 30 degrees cooler than the adjacent solder joints.





Figure 61. Typical Tin Lead (SnPb) Solder Heating Profile

## TYPICAL SOLDER HEATING PROFILE (continued)



**Figure 62. Typical Pb-Free Solder Heating Profile**

Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate ( $T_{s_{max}}$ to $T_p$ )	3°C/second max
Preheat Temperature Min ( $T_{s_{min}}$ ) Temperature Max ( $T_{s_{max}}$ ) Time ( $t_{s_{min}}$ to $t_{s_{max}}$ )	150°C 200°C 60–180 seconds
Time maintained above Temperature ( $T_T$ ) Time ( $t_T$ )	217°C 60–150 seconds
Peak Classification Temperature ( $T_p$ )	260°C +5/-0
Time within 5°C of actual Peak Temperature ( $t_p$ )	20–40 seconds
Ramp-Down Rate	6°C/second max
Time 25°C to Peak Temperature	8 minutes max

## AMBIENT MOUNTING DATA


Data shown for thermal resistance junction-to-ambient ( $R_{\theta JA}$ ) for the mountings shown is to be used as typical guideline values for preliminary engineering or in case the tie point temperature cannot be measured.

### TYPICAL VALUES FOR $R_{\theta JA}$ IN STILL AIR

Mounting Method		Lead Length, L (IN)				Units
		1/8	1/4	1/2	3/4	
1	$R_{\theta JA}$	50	51	53	55	$^{\circ}\text{C/W}$
2		58	59	61	63	$^{\circ}\text{C/W}$
3		28				$^{\circ}\text{C/W}$


#### MOUNTING METHOD 1

P.C. Board Where Available Copper Surface area is small.




#### MOUNTING METHOD 2

Vector Push-In Terminals T-28



#### MOUNTING METHOD 3

P.C. Board with  
1-1/2" x 1-1/2" Copper Surface



# Humidity Indicator Card: Type HIC-0560

## Objective

The objective of this information brief is to provide the customer with a general understanding of the humidity indicator cards (HIC) basic functions and a reaction plan based on the level of dryness as indicated on the card.

## Introduction

The HIC is printed with moisture sensitive spots which will respond to variations of different levels of humidity with perceptible change in color typically from blue (dry) to pink (wet). The HIC is packed inside moisture barrier bags, which monitor the moisture inside the barrier bag. When the bag is opened, the HIC can be examined to determine the degree of dryness of the parts inside the bag.

## Humidity Indicator Cards: HIC-0515 and HIC-0560

Excess humidity in the dry pack is noted by the HIC. It can occur due to misprocessing (e.g. missing or inadequate desiccant), mishandling (e.g. tears or rips in the moisture barrier bag) or improper storage.

The HIC should be read immediately upon removal from the moisture barrier bag. For best accuracy, the HIC should be read at  $23 \pm 5^\circ\text{C}$ . The following conditions apply regardless of the storage time (whether or not the shelf life has exceeded).




Figure 63. Humidity Indicator Card

Table 2: HIC Conditions and Corresponding Actions for HIC-0560

HIC Conditions	5%	10%	60%	Action	Remarks
Condition 1	Blue	Blue	Blue	No bake	Parts are dry
Condition 2	Pink	Blue	Blue	No bake	Only indicates that parts have 5% level of moisture
Condition 3	Pink	Pink	Blue	Bake required, refer to Table 2	Bake parts MSL levels 2a, 3, 4, 5, and 5a No need to bake MSL level 2
Condition 4	Pink	Pink	Pink	Bake required, refer to Table 2	All were parts were affected by moisture

### Bake Duration for Exposed Parts

AMIS recommends that bake duration of exposed parts should comply with the existing provisions as mandated by Joint Industry Standard IPC/JEDEC-STD-033B entitled

“Handling, Packing and Use of Moisture/Reflow Sensitive Surface Mount Devices” Bake Duration for Exposed Parts as shown in Table 3.

**Table 3: Reference Conditions for Drying Mounted or Unmounted SMD Packages**  
(User bake: floor life beings counting at time = 0 after bake)

Package Body	Level	Bake @ 125°C		Bake @ 90°C ≤ 5% RH		Bake @ 40°C ≤ 5% RH	
		Exceeding Floor Life by > 72 h	Exceeding Floor Life by > 72 h	Exceeding Floor Life by > 72 h	Exceeding Floor Life by > 72 h	Exceeding Floor Life by > 72 h	Exceeding Floor Life by > 72 h
Thickness ≤ 1.4mm	2	5 hours	3 hours	17 hours	11 hours	8 days	5 days
	2a	7 hours	5 hours	23 hours	13 hours	9 days	7 days
	3	9 hours	7 hours	33 hours	23 hours	13 days	9 days
	4	11 hours	7 hours	37 hours	23 hours	15 days	9 days
	5	12 hours	7 hours	41 hours	24 hours	17 days	10 days
	5a	16 hours	10 hours	54 hours	24 hours	22 days	10 days
Thickness > 1.4mm ≤ 2.0mm	2	18 hours	15 hours	63 hours	2 days	25 days	20 days
	2a	21 hours	16 hours	3 days	2 days	29 days	22 days
	3	27 hours	17 hours	4 days	2 days	37 days	23 days
	4	34 hours	20 hours	5 days	3 days	47 days	28 days
	5	40 hours	25 hours	6 days	4 days	57 days	35 days
	5a	48 hours	40 hours	8 days	6 days	79 days	56 days
Thickness > 2.0mm ≤ 4.5mm	2	48 hours	48 hours	10 days	7 days	79 days	67 days
	2a	48 hours	48 hours	10 days	7 days	79 days	67 days
	3	48 hours	48 hours	10 days	8 days	79 days	67 days
	4	48 hours	48 hours	10 days	10 days	79 days	67 days
	5	48 hours	48 hours	10 days	10 days	79 days	67 days
	5a	48 hours	48 hours	10 days	10 days	79 days	67 days
BGA package > 17mm x 17mm or any stacked die package (Note 12)	2-6	96 hours	As above per package thickness and moisture level	Not applicable	As above per package thickness and moisture level	Not applicable	As above per package thickness and moisture level

#### NOTES:

11. Table 3 is based on worst-case molded lead frame SMD packages. Users may reduce the actual back time if technically justified (e.g. absorption/desorption data, etc.). In most cases it is applicable to other nonhermetic surface mount SMD packages.
12. For BGA packages > 17mm x >17 mm that do not have internal planes that block the moisture diffusion path in the substrate they may use bake times based on the thickness/moisture level portion of the table.



## Sales and Design Assistance from ON Semiconductor

### ON Semiconductor Distribution Partners

Allied Electronics	www.alliedelec.com	(800) 433-5700
Arrow Electronics	www.arrow.com	(800) 777-2776
Avnet	www.em.avnet.com	(800) 332-8638
Chip One Stop, Inc.	www.chip1stop.com/maker/on	(81) 45 470 8771
Daiwa Distribution Ltd.	www.daiwahk.com	(852) 2341 3351
Digi-Key	www.digikey.com	(800) 344-4539
EBV Elektronik	www.ebv.com/en/locations.html	(49) 8121 774-0
Fuji Electronics Co., Ltd.	www.fujiele.co.jp	(81) 3 3814 1770
Future & F&I Electronics	www.futureelectronics.com/contact	1-800-FUTURE1 (388-8731)
KH Electronics Inc.	www.khelec.com/kor	(82) 42 471 8521
Mitsui Electronics Inc.	www.btel.co.jp	(81) 3 6403 5900
Mouser Electronics	www.mouser.com	(800) 346-6873
Newark/Farnell	www.farnell.com/onsemi	(800) 4-NEWARK
OS Electronics Co., Ltd.	www.oselec.jp	Japanese: (81) 3 3255 5985 Other Languages: (81) 3 3255 6066
Promate Electronic Co.	www.promate.com.tw	(886) 2 2659 0303
RS Components KK	jp.rs-online.com	(81) 45 335 8550
Segyung Bristestone Co.	www.bristestone.com	(82) 2 3218 1511
Serial AMSC	www.serialsystem.jp	(81) 3 5302 1569
Serial Microelectronics, HK	www.serialsys.com.hk	(852) 2790 8220
Taewon Inc.	www.taewon.net	(82) 2 6679 9000
World Peace Industries Co.	www.wpi-group.com	(852) 2365 4860
WT Microelectronics Co.	www.wtmec.com	(852) 2950 0820
Yosun Electronics	www.yosun.com.tw	(886) 2 2659 8168

### INTERNATIONAL

<b>GREATER CHINA</b>	Beijing	86-10-8577-8200
	Hong Kong	852-2689-0088
	Shenzhen	86-755-8209-1128
	Shanghai	86-21-5131-7168
	Taipei, Taiwan	886-2-2377-9911
<b>FRANCE</b>	Paris	33 (0)1 39-26-41-00
<b>GERMANY</b>	Munich	49 (0) 89-93-0808-0
<b>INDIA</b>	Bangalore	91-98-808-86706
<b>ISRAEL</b>	Raanana	972 (0) 9-9609-111
<b>ITALY</b>	Milan	39 02 9239311
<b>JAPAN</b>	Tokyo	81-3-5817-1050
<b>KOREA</b>	Seoul	82-2-2190-3500
<b>MALAYSIA</b>	Penang	60-4-6463877
<b>SINGAPORE</b>	Singapore	65-6484-8603
<b>SLOVAKIA</b>	Piestany	421 33 790 2450
<b>UNITED KINGDOM</b>	Slough	44 (0) 1753 70 1676

### AMERICAS REP FIRMS

<b>Alabama</b>	Huntsville	e-Components	(256) 533-2444
<b>Brazil</b>	Countrywide	Ammon & Rizo	(+55) 11-4688-1960
<b>California</b>	Bay Area	Electec	(408) 496-0706
	Southern California	Tech Coast Sales	(949) 305-6869
<b>Canada</b>	Eastern Canada	Astec	(905) 607-1444
<b>Connecticut</b>	Statewide	Paragon Electronic Systems	(603) 645-7630
<b>Florida</b>	Statewide	e-Components	(888) 468-2444
<b>Georgia</b>	Atlanta	e-Components	(888) 468-2444
<b>Illinois</b>	Hoffman Estates	Stan Clothier Company	(847) 781-4010
<b>Indiana</b>	Fishers	Bear VAI	(317) 570-0707
<b>Kansas</b>	Overland Park	Stan Clothier Company	(913) 894-1675
<b>Maine</b>	Statewide	Paragon Electronic Systems	(603) 645-7630
<b>Maryland</b>	Columbia	Third Wave Solutions	(410) 290-5990
<b>Massachusetts</b>	Statewide	Paragon Electronic Systems	(603) 645-7630
<b>Mexico</b>	Countrywide	Ammon & Rizo	(+55) 11-4688-1960
<b>Michigan</b>	St. Joseph	Bear VAI	(440) 526-1991
<b>Minnesota</b>	Eden Prairie	Stan Clothier Company	(952) 944-3456
<b>Missouri</b>	St. Charles	Stan Clothier Company	(636) 916-3777
<b>New Hampshire</b>	Statewide	Paragon Electronic Systems	(603) 645-7630
<b>New Jersey</b>	Statewide	S.J. Metro	(516) 942-3232
<b>New York</b>	Binghamton	TriTech - Full Line Rep	(607) 722-3580
	Jericho	S.J. Metro	(516) 942-3232
	Rochester	TriTech - Full Line Rep	(585) 385-6500
<b>North Carolina</b>	Raleigh	e-Components	(888) 468-2444
<b>Ohio</b>	Brecksville	Bear VAI Technology	(440) 526-1991
<b>Puerto Rico</b>	Countrywide	e-Components	(888) 468-2444
<b>Rhode Island</b>	Statewide	Paragon Electronic Systems	(603) 645-7630
<b>Vermont</b>	Statewide	Paragon Electronic Systems	(603) 645-7630
<b>Wisconsin</b>	Evansville	Stan Clothier Company	(608) 882-0686
	Oconomowoc	Stan Clothier Company	(608) 882-0686

For a comprehensive listing of  
ON Semiconductor Sales Offices, please visit:  
**www.onsemi.com/salesupport**



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada.

Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910

Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative