

# NL17SZ126

## Non-inverting 3-State Buffer

The NL17SZ126 is a high performance dual noninverting buffer operating from a 2.3 V to 5.5 V supply.

- Extremely High Speed:  $t_{PD}$  2.6 ns (typical) at  $V_{CC} = 5$  V
- Designed for 2.3 V to 5.5 V  $V_{CC}$  Operation
- Over Voltage Tolerant Inputs and Outputs
- LVTTL Compatible – Interface Capability With 5 V TTL Logic with  $V_{CC} = 3$  V
- LVCMOS Compatible
- 24 mA Balanced Output Sink and Source Capability
- Near Zero Static Supply Current Substantially Reduces System Power Requirements
- 3-State OE Input is Active HIGH
- Replacement for NC7SZ126
- Chip Complexity = 36 Feet




Figure 1. Pinout (Top View)




Figure 2. Logic Symbol




**ON Semiconductor®**

<http://onsemi.com>

### MARKING DIAGRAMS



SC70-5/SC-88A/SOT-353  
DF SUFFIX  
CASE 419A



d = Date Code

### PIN ASSIGNMENT

| PIN | ASSIGNMENT |
|-----|------------|
| 1   | OE         |
| 2   | IN A       |
| 3   | GND        |
| 4   | OUT Y      |
| 5   | $V_{CC}$   |

### FUNCTION TABLE

| OE Input | A Input | Y Output |
|----------|---------|----------|
| H        | L       | L        |
| H        | H       | H        |
| L        | X       | Z        |

X = Don't Care

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

## MAXIMUM RATINGS

| Symbol           | Parameter                                       | Value                                                                                | Unit                   |
|------------------|-------------------------------------------------|--------------------------------------------------------------------------------------|------------------------|
| V <sub>CC</sub>  | DC Supply Voltage                               | − 0.5 to + 7.0                                                                       | V                      |
| V <sub>IN</sub>  | DC Input Voltage                                | − 0.5 to + 7.0                                                                       | V                      |
| V <sub>OUT</sub> | DC Output Voltage                               | − 0.5 to + 7.0                                                                       | V                      |
| I <sub>IK</sub>  | DC Input Diode Current                          | − 50                                                                                 | mA                     |
| I <sub>OK</sub>  | DC Output Diode Current                         | − 50                                                                                 | mA                     |
| I <sub>OUT</sub> | DC Output Sink Current                          | ± 50                                                                                 | mA                     |
| I <sub>CC</sub>  | DC Supply Current per Supply Pin                | ± 100                                                                                | mA                     |
| T <sub>STG</sub> | Storage Temperature Range                       | − 65 to + 150                                                                        | °C                     |
| T <sub>L</sub>   | Lead Temperature, 1 mm from Case for 10 Seconds | 260                                                                                  | °C                     |
| T <sub>J</sub>   | Junction Temperature Under Bias                 | + 150                                                                                | °C                     |
| θ <sub>JA</sub>  | Thermal Resistance                              | SC-70/SC-88A                                                                         | °C/W                   |
| P <sub>D</sub>   | Power Dissipation in Still Air at 85°C          | SC-70/SC-88A                                                                         | mW                     |
| MSL              | Moisture Sensitivity                            | Level 1                                                                              |                        |
| F <sub>R</sub>   | Flammability Rating                             | Oxygen Index: 28 to 34                                                               | UL 94 V-0 @ 0.125 in   |
| V <sub>ESD</sub> | ESD Withstand Voltage                           | Human Body Model (Note 2)<br>Machine Model (Note 3)<br>Charged Device Model (Note 4) | > 2000<br>> 200<br>N/A |

Maximum Ratings are those values beyond which damage to the device may occur. Exposure to these conditions or conditions beyond those indicated may adversely affect device reliability. Functional operation under absolute maximum-rated conditions is not implied. Functional operation should be restricted to the Recommended Operating Conditions.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2-ounce copper trace with no air flow.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to JESD22-C101-A.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Parameter                   | Min                                                                | Max  | Unit |
|---------------------------------|-----------------------------|--------------------------------------------------------------------|------|------|
| V <sub>CC</sub>                 | DC Supply Voltage           | 2.0                                                                | 5.5  | V    |
| V <sub>IN</sub>                 | DC Input Voltage            | 0                                                                  | 5.5  | V    |
| V <sub>OUT</sub>                | DC Output Voltage           | 0                                                                  | 5.5  | V    |
| T <sub>A</sub>                  | Operating Temperature Range | − 40                                                               | + 85 | °C   |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise and Fall Time    | V <sub>CC</sub> = 3.0 V ± 0.3 V<br>V <sub>CC</sub> = 5.0 V ± 0.5 V |      | ns/V |
|                                 |                             | 0                                                                  | 100  |      |
|                                 |                             | 0                                                                  | 20   |      |

## DEVICE JUNCTION TEMPERATURE VERSUS TIME TO 0.1% BOND FAILURES

| Junction Temperature °C | Time, Hours | Time, Years |
|-------------------------|-------------|-------------|
| 80                      | 1,032,200   | 117.8       |
| 90                      | 419,300     | 47.9        |
| 100                     | 178,700     | 20.4        |
| 110                     | 79,600      | 9.4         |
| 120                     | 37,000      | 4.2         |
| 130                     | 17,800      | 2.0         |
| 140                     | 8,900       | 1.0         |




Figure 3. Failure Rate versus Time Junction Temperature

## DC ELECTRICAL CHARACTERISTICS

| Symbol           | Parameter                                                                        | Condition                                                                                                                                                           | V <sub>CC</sub><br>(V)                        | T <sub>A</sub> = 25°C                                    |                                                    |                                          | –40°C ≤ T <sub>A</sub> ≤ 85°C                            |                                          | Unit |
|------------------|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|----------------------------------------------------------|----------------------------------------------------|------------------------------------------|----------------------------------------------------------|------------------------------------------|------|
|                  |                                                                                  |                                                                                                                                                                     |                                               | Min                                                      | Typ                                                | Max                                      | Min                                                      | Max                                      |      |
| V <sub>IH</sub>  | High-Level Input Voltage                                                         |                                                                                                                                                                     | 2.3 to 5.5                                    | 0.7 V <sub>CC</sub>                                      |                                                    |                                          | 0.7 V <sub>CC</sub>                                      |                                          | V    |
| V <sub>IL</sub>  | Low-Level Input Voltage                                                          |                                                                                                                                                                     | 2.3 to 5.5                                    |                                                          |                                                    | 0.3 V <sub>CC</sub>                      |                                                          | 0.3 V <sub>CC</sub>                      | V    |
| V <sub>OH</sub>  | High-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IH</sub>                   | I <sub>OH</sub> = 100 μA<br>I <sub>OH</sub> = –8 mA<br>I <sub>OH</sub> = –12 mA<br>I <sub>OH</sub> = –16 mA<br>I <sub>OH</sub> = –24 mA<br>I <sub>OH</sub> = –32 mA | 2.3 to 5.5<br>2.3<br>2.7<br>3.0<br>3.0<br>4.5 | V <sub>CC</sub> – 0.1<br>1.9<br>2.2<br>2.4<br>2.7<br>3.8 | V <sub>CC</sub><br>2.1<br>2.4<br>2.7<br>2.5<br>4.0 |                                          | V <sub>CC</sub> – 0.1<br>1.9<br>2.2<br>2.4<br>2.3<br>3.8 |                                          | V    |
| V <sub>OL</sub>  | Low-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OL</sub> = 100 μA<br>I <sub>OL</sub> = 8 mA<br>I <sub>OL</sub> = 12 mA<br>I <sub>OL</sub> = 16 mA<br>I <sub>OL</sub> = 24 mA<br>I <sub>OL</sub> = 32 mA      | 2.3 to 5.5<br>2.3<br>2.7<br>3.0<br>3.0<br>4.5 |                                                          | 0.20<br>0.22<br>0.28<br>0.38<br>0.55<br>0.42       | 0.1<br>0.3<br>0.4<br>0.4<br>0.55<br>0.55 |                                                          | 0.1<br>0.3<br>0.4<br>0.4<br>0.55<br>0.55 | V    |
| I <sub>IN</sub>  | Input Leakage Current                                                            | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                                                                            | 0 to 5.5                                      |                                                          |                                                    | ±0.1                                     |                                                          | ±1.0                                     | μA   |
| I <sub>OFF</sub> | Power Off-Output Leakage Current                                                 | V <sub>OUT</sub> = 5.5 V                                                                                                                                            | 0                                             |                                                          |                                                    | 1                                        |                                                          | 10                                       | μA   |
| I <sub>CC</sub>  | Quiescent Supply Current                                                         | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                                                                            | 5.5                                           |                                                          |                                                    | 1                                        |                                                          | 10                                       | μA   |
| I <sub>OZ</sub>  | 3-State Output Leakage                                                           | 0 V ≤ V <sub>OUT</sub> ≤ 5.5 V<br>V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub>                                                                              | 2.3 to 5.5                                    |                                                          |                                                    | ±0.5                                     |                                                          | ±5                                       | μA   |

AC ELECTRICAL CHARACTERISTICS (t<sub>R</sub> = t<sub>F</sub> = 3.0 ns)

| Symbol                               | Parameter                                                       | Condition                                               | V <sub>CC</sub><br>(V) | T <sub>A</sub> = 25°C |     |     | –40°C ≤ T <sub>A</sub> ≤ 85°C |     | Unit |
|--------------------------------------|-----------------------------------------------------------------|---------------------------------------------------------|------------------------|-----------------------|-----|-----|-------------------------------|-----|------|
|                                      |                                                                 |                                                         |                        | Min                   | Typ | Max | Min                           | Max |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay<br>AN to YN<br>(Figures 4, and 5,<br>Table 1) | R <sub>L</sub> = 1 MΩ    C <sub>L</sub> = 15 pF         | 2.5 ± 0.2              | 1.0                   |     | 7.5 | 1.0                           | 8   | ns   |
|                                      |                                                                 | R <sub>L</sub> = 1 MΩ    C <sub>L</sub> = 15 pF         | 3.3 ± 0.3              | 0.8                   |     | 5.2 | 0.8                           | 5.5 |      |
|                                      |                                                                 | R <sub>L</sub> = 500 Ω    C <sub>L</sub> = 50 pF        |                        | 1.2                   |     | 5.7 | 1.2                           | 6.0 |      |
| t <sub>PZH</sub><br>t <sub>PZL</sub> | Output Enable Time<br>(Figures 6, 7 and 8,<br>Table 1)          | R <sub>L</sub> = 1 MΩ    C <sub>L</sub> = 15 pF         | 5.0 ± 0.5              | 0.5                   |     | 4.5 | 0.5                           | 4.8 | ns   |
|                                      |                                                                 | R <sub>L</sub> = 500 Ω    C <sub>L</sub> = 50 pF        |                        | 0.8                   |     | 5.0 | 0.8                           | 5.3 |      |
|                                      |                                                                 |                                                         |                        |                       |     |     |                               |     |      |
| t <sub>PZH</sub><br>t <sub>PZL</sub> | Output Enable Time<br>(Figures 6, 7 and 8,<br>Table 1)          | R <sub>L</sub> = 250 Ω    C <sub>L</sub> = 50 pF        | 2.5 ± 0.2              | 1.8                   |     | 8.5 | 1.8                           | 9.0 | ns   |
|                                      |                                                                 |                                                         | 3.3 ± 0.3              | 1.2                   |     | 6.2 | 1.2                           | 6.5 |      |
|                                      |                                                                 |                                                         | 5.0 ± 0.5              | 0.8                   |     | 5.5 | 0.8                           | 5.8 |      |
| t <sub>PZH</sub><br>t <sub>PZL</sub> | Output Enable Time<br>(Figures 6, 7 and 8,<br>Table 1)          | R <sub>L</sub> and R1 = 500 Ω    C <sub>L</sub> = 50 pF | 2.5 ± 0.2              | 1.5                   |     | 8.0 | 1.5                           | 8.5 | ns   |
|                                      |                                                                 |                                                         | 3.3 ± 0.3              | 0.8                   |     | 5.7 | 0.8                           | 6.0 |      |
|                                      |                                                                 |                                                         | 5.0 ± 0.5              | 0.3                   |     | 4.7 | 0.3                           | 5.0 |      |

## CAPACITIVE CHARACTERISTICS

| Symbol           | Parameter                                 | Condition                                                                                                                                            | Typical | Unit |
|------------------|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------|------|
| C <sub>IN</sub>  | Input Capacitance                         | V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 0 V or V <sub>CC</sub>                                                                                     | 2.5     | pF   |
| C <sub>OUT</sub> | Output Capacitance                        | V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 0 V or V <sub>CC</sub>                                                                                     | 2.5     | pF   |
| C <sub>PD</sub>  | Power Dissipation Capacitance<br>(Note 5) | 10 MHz, V <sub>CC</sub> = 3.3 V, V <sub>I</sub> = 0 V or V <sub>CC</sub><br>10 MHz, V <sub>CC</sub> = 5.5 V, V <sub>I</sub> = 0 V or V <sub>CC</sub> | 9<br>11 | pF   |

5. C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I<sub>CC(OPR)</sub> = C<sub>PD</sub> • V<sub>CC</sub> • f<sub>in</sub> + I<sub>CC</sub>. C<sub>PD</sub> is used to determine the no-load dynamic power consumption; P<sub>D</sub> = C<sub>PD</sub> • V<sub>CC</sub><sup>2</sup> • f<sub>in</sub> + I<sub>CC</sub> • V<sub>CC</sub>.






Figure 4. Switching Waveform




\*Includes all probe and jig capacitance.  
A 1-MHz square input wave is recommended for propagation delay tests.

Figure 5.  $T_{PLH}$  or  $T_{PHL}$



A 1-MHz square input wave is recommended for propagation delay tests.

Figure 6.  $T_{PZL}$  or  $T_{PLZ}$



A 1-MHz square input wave is recommended for propagation delay tests.

Figure 7.  $T_{PZH}$  or  $T_{PHZ}$




Figure 8. AC Output Enable and Disable Waveform

# NL17SZ126

**Table 1. Output Enable and Disable Times**

$t_R = t_F = 2.5 \text{ ns}$ , 10% to 90%;  $f = 1 \text{ MHz}$ ;  $t_W = 500 \text{ ns}$

| Symbol   | $V_{CC}$                          |                 |                                   |
|----------|-----------------------------------|-----------------|-----------------------------------|
|          | $3.3 \text{ V} \pm 0.3 \text{ V}$ | $2.7 \text{ V}$ | $2.5 \text{ V} \pm 0.2 \text{ V}$ |
| $V_{mi}$ | 1.5 V                             | 1.5 V           | $V_{CC}/2$                        |
| $V_{mo}$ | 1.5 V                             | 1.5 V           | $V_{CC}/2$                        |

## DEVICE ORDERING INFORMATION

| Device Order Number | Device Nomenclature     |                          |                       |            |                 |                |                      | Package Type              | Tape and Reel Size         |
|---------------------|-------------------------|--------------------------|-----------------------|------------|-----------------|----------------|----------------------|---------------------------|----------------------------|
|                     | Logic Circuit Indicator | No. of Gates per Package | Temp Range Identifier | Technology | Device Function | Package Suffix | Tape and Reel Suffix |                           |                            |
| NL17SZ126           | NL                      | 1                        | 7                     | SZ         | 126             | DF             | T2                   | SC70-5/SC-88A/<br>SOT-353 | 178 mm (7"),<br>3000 Units |

The diagram illustrates the layout of a tape reel. It shows a cross-section of the tape on the left, with labels for 'CAVITY TAPE' and 'TOP TAPE'. The main body of the reel is divided into three sections: a 'TAPE TRAILER (Connected to Reel Hub) NO COMPONENTS 160 mm MIN', a central section for 'COMPONENTS' with an arrow indicating the 'DIRECTION OF FEED', and a 'TAPE LEADER NO COMPONENTS 400 mm MIN'. The tape is shown with dashed lines representing component pockets and solid lines representing the tape edges and holes.

TAPE DIMENSIONS mm

4.00

2.00

4.00

8.00  $\pm 0.30$

$\varnothing 1.50$  TYP

1.75

3.50  $\pm 0.50$

$\varnothing 1.00$  MIN

DIRECTION OF FEED

1

6




Figure 11. Reel Dimensions

REEL DIMENSIONS

| Tape Size | T and R Suffix | A Max          | G                                                     | t Max                |
|-----------|----------------|----------------|-------------------------------------------------------|----------------------|
| 8 mm      | T1, T2         | 178 mm<br>(7") | 8.4 mm, + 1.5 mm, -0.0<br>(0.33 in + 0.059 in, -0.00) | 14.4 mm<br>(0.56 in) |





Figure 12. Reel Winding Direction

# NL17SZ126



## PACKAGE DIMENSIONS

SC70-5/SC-88A/SOT-353  
DF SUFFIX  
5-LEAD PACKAGE  
CASE 419A-02  
ISSUE F



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH.
  3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |



ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

## PUBLICATION ORDERING INFORMATION

### Literature Fulfillment:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: ONlit@hibbertco.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center  
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031  
Phone: 81-3-5740-2700  
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.