



## Power MOSFET

### PRODUCT SUMMARY

|                           |                        |      |
|---------------------------|------------------------|------|
| $V_{DS}$ (V)              | 500                    |      |
| $R_{DS(on)}$ ( $\Omega$ ) | $V_{GS} = 10\text{ V}$ | 0.85 |
| $Q_g$ (Max.) (nC)         | 38                     |      |
| $Q_{gs}$ (nC)             | 9.0                    |      |
| $Q_{gd}$ (nC)             | 18                     |      |
| Configuration             | Single                 |      |



### FEATURES

- Low Gate Charge  $Q_g$  Results in Simple Drive Requirement
- Improved Gate, Avalanche and Dynamic  $dV/dt$  Ruggedness
- Fully Characterized Capacitance and Avalanche Voltage and Current
- Effective  $C_{OSS}$  Specified
- Compliant to RoHS Directive 2002/95/EC



**RoHS\***  
COMPLIANT

### APPLICATIONS

- Switch Mode Power Supply (SMPS)
- Uninterruptable Power Supply
- High Speed Power Switching

### TYPICAL SMPS TOPOLOGIES

- Two Transistor Forward
- Half Bridge
- Full Bridge

### ORDERING INFORMATION

|                |                           |
|----------------|---------------------------|
| Package        | TO-220AB                  |
| Lead (Pb)-free | IRF840APbF<br>SiHF840A-E3 |
| SnPb           | IRF840A<br>SiHF840A       |

### ABSOLUTE MAXIMUM RATINGS ( $T_C = 25\text{ }^\circ\text{C}$ , unless otherwise noted)

| PARAMETER                                        | SYMBOL           | LIMIT                             | UNIT                |
|--------------------------------------------------|------------------|-----------------------------------|---------------------|
| Drain-Source Voltage                             | $V_{DS}$         | 500                               | V                   |
| Gate-Source Voltage                              | $V_{GS}$         | $\pm 30$                          |                     |
| Continuous Drain Current                         | $I_D$            | $T_C = 25\text{ }^\circ\text{C}$  | A                   |
|                                                  |                  | $T_C = 100\text{ }^\circ\text{C}$ |                     |
| Pulsed Drain Current <sup>a</sup>                | $I_{DM}$         | 32                                |                     |
| Linear Derating Factor                           |                  | 1.0                               | W/ $^\circ\text{C}$ |
| Single Pulse Avalanche Energy <sup>b</sup>       | $E_{AS}$         | 510                               | mJ                  |
| Repetitive Avalanche Current <sup>a</sup>        | $I_{AR}$         | 8.0                               | A                   |
| Repetitive Avalanche Energy <sup>a</sup>         | $E_{AR}$         | 13                                | mJ                  |
| Maximum Power Dissipation                        | $P_D$            | 125                               | W                   |
| Peak Diode Recovery $dV/dt$ <sup>c</sup>         | $dV/dt$          | 5.0                               | V/ns                |
| Operating Junction and Storage Temperature Range | $T_J, T_{stg}$   | - 55 to + 150                     | $^\circ\text{C}$    |
| Soldering Recommendations (Peak Temperature)     | for 10 s         | 300 <sup>d</sup>                  |                     |
| Mounting Torque                                  | 6-32 or M3 screw | 10                                | lbf · in            |
|                                                  |                  | 1.1                               | N · m               |

#### Notes

- Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- $V_{DD} = 50\text{ V}$ , starting  $T_J = 25\text{ }^\circ\text{C}$ ,  $L = 16\text{ mH}$ ,  $R_g = 25\text{ }\Omega$ ,  $I_{AS} = 8.0\text{ A}$  (see fig. 12).
- $I_{SD} \leq 8.0\text{ A}$ ,  $dI/dt \leq 100\text{ A}/\mu\text{s}$ ,  $V_{DD} \leq V_{DS}$ ,  $T_J \leq 150\text{ }^\circ\text{C}$ .
- 1.6 mm from case.

\* Pb containing terminations are not RoHS compliant, exemptions may apply

**THERMAL RESISTANCE RATINGS**

| PARAMETER                           | SYMBOL     | TYP. | MAX. | UNIT |
|-------------------------------------|------------|------|------|------|
| Maximum Junction-to-Ambient         | $R_{thJA}$ | -    | 62   | °C/W |
| Case-to-Sink, Flat, Greased Surface | $R_{thCS}$ | 0.50 | -    |      |
| Maximum Junction-to-Case (Drain)    | $R_{thJC}$ | -    | 1.0  |      |

**SPECIFICATIONS** ( $T_J = 25\text{ °C}$ , unless otherwise noted)

| PARAMETER                                 | SYMBOL                           | TEST CONDITIONS                                                                                                                                         |                                                                                  | MIN. | TYP. | MAX.  | UNIT |
|-------------------------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|------|------|-------|------|
| Static                                    |                                  |                                                                                                                                                         |                                                                                  |      |      |       |      |
| Drain-Source Breakdown Voltage            | V <sub>DS</sub>                  | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                                                                                                          |                                                                                  | 500  | -    | -     | V    |
| V <sub>DS</sub> Temperature Coefficient   | ΔV <sub>DS</sub> /T <sub>J</sub> | Reference to 25 °C, I <sub>D</sub> = 1 mA                                                                                                               |                                                                                  | -    | 0.58 | -     | V/°C |
| Gate-Source Threshold Voltage             | V <sub>GS(th)</sub>              | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA                                                                                             |                                                                                  | 2.0  | -    | 4.0   | V    |
| Gate-Source Leakage                       | I <sub>GSS</sub>                 | V <sub>GS</sub> = ± 30 V                                                                                                                                |                                                                                  | -    | -    | ± 100 | nA   |
| Zero Gate Voltage Drain Current           | I <sub>DSS</sub>                 | V <sub>DS</sub> = 500 V, V <sub>GS</sub> = 0 V                                                                                                          |                                                                                  | -    | -    | 25    | μA   |
|                                           |                                  | V <sub>DS</sub> = 400 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 125 °C                                                                                 |                                                                                  | -    | -    | 250   |      |
| Drain-Source On-State Resistance          | R <sub>DS(on)</sub>              | V <sub>GS</sub> = 10 V                                                                                                                                  | I <sub>D</sub> = 4.8 A <sup>b</sup>                                              | -    | -    | 0.85  | Ω    |
| Forward Transconductance                  | g <sub>fs</sub>                  | V <sub>DS</sub> = 50 V, I <sub>D</sub> = 4.8 A <sup>b</sup>                                                                                             |                                                                                  | 3.7  | -    | -     | S    |
| Dynamic                                   |                                  |                                                                                                                                                         |                                                                                  |      |      |       |      |
| Input Capacitance                         | C <sub>iss</sub>                 | V <sub>GS</sub> = 0 V,<br>V <sub>DS</sub> = 25 V,<br>f = 1.0 MHz, see fig. 5                                                                            |                                                                                  | -    | 1018 | -     | pF   |
| Output Capacitance                        | C <sub>oss</sub>                 |                                                                                                                                                         |                                                                                  | -    | 155  | -     |      |
| Reverse Transfer Capacitance              | C <sub>rss</sub>                 |                                                                                                                                                         |                                                                                  | -    | 8.0  | -     |      |
| Output Capacitance                        | C <sub>oss</sub>                 | V <sub>GS</sub> = 0 V; V <sub>DS</sub> = 1.0 V, f = 1.0 MHz                                                                                             |                                                                                  |      | 1490 |       |      |
| Output Capacitance                        | C <sub>oss</sub>                 | V <sub>GS</sub> = 0 V; V <sub>DS</sub> = 400 V, f = 1.0 MHz                                                                                             |                                                                                  |      | 42   |       |      |
| Effective Output Capacitance              | C <sub>oss eff.</sub>            | V <sub>GS</sub> = 0 V; V <sub>DS</sub> = 0 V to 400 V <sup>c</sup>                                                                                      |                                                                                  |      | 56   |       |      |
| Total Gate Charge                         | Q <sub>g</sub>                   | V <sub>GS</sub> = 10 V                                                                                                                                  | I <sub>D</sub> = 8 A, V <sub>DS</sub> = 400 V,<br>see fig. 6 and 13 <sup>b</sup> | -    | -    | 38    | nC   |
| Gate-Source Charge                        | Q <sub>gs</sub>                  |                                                                                                                                                         |                                                                                  | -    | -    | 9.0   |      |
| Gate-Drain Charge                         | Q <sub>gd</sub>                  |                                                                                                                                                         |                                                                                  | -    | -    | 18    |      |
| Turn-On Delay Time                        | t <sub>d(on)</sub>               | V <sub>DD</sub> = 250 V, I <sub>D</sub> = 8 A<br>R <sub>g</sub> = 9.1 Ω, R <sub>D</sub> = 31 Ω, see fig. 10 <sup>b</sup>                                |                                                                                  | -    | 11   | -     | ns   |
| Rise Time                                 | t <sub>r</sub>                   |                                                                                                                                                         |                                                                                  | -    | 23   | -     |      |
| Turn-Off Delay Time                       | t <sub>d(off)</sub>              |                                                                                                                                                         |                                                                                  | -    | 26   | -     |      |
| Fall Time                                 | t <sub>f</sub>                   |                                                                                                                                                         |                                                                                  | -    | 19   | -     |      |
| Drain-Source Body Diode Characteristics   |                                  |                                                                                                                                                         |                                                                                  |      |      |       |      |
| Continuous Source-Drain Diode Current     | I <sub>S</sub>                   | MOSFET symbol showing the integral reverse p - n junction diode<br> |                                                                                  | -    | -    | 8.0   | A    |
| Pulsed Diode Forward Current <sup>a</sup> | I <sub>SM</sub>                  |                                                                                                                                                         |                                                                                  | -    | -    | 32    |      |
| Body Diode Voltage                        | V <sub>SD</sub>                  | T <sub>J</sub> = 25 °C, I <sub>S</sub> = 8 A, V <sub>GS</sub> = 0 V <sup>b</sup>                                                                        |                                                                                  | -    | -    | 2.0   | V    |
| Body Diode Reverse Recovery Time          | t <sub>rr</sub>                  | T <sub>J</sub> = 25 °C, I <sub>F</sub> = 8 A, dI/dt = 100 A/μs <sup>b</sup>                                                                             |                                                                                  | -    | 422  | 633   | ns   |
| Body Diode Reverse Recovery Charge        | Q <sub>rr</sub>                  |                                                                                                                                                         |                                                                                  | -    | 2.16 | 3.24  | μC   |
| Forward Turn-On Time                      | t <sub>on</sub>                  | Intrinsic turn-on time is negligible (turn-on is dominated by L <sub>S</sub> and L <sub>D</sub> )                                                       |                                                                                  |      |      |       |      |

**Notes**

- a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).  
b. Pulse width  $\leq 300\text{ }\mu\text{s}$ ; duty cycle  $\leq 2\%$ .  
c.  $C_{oss\text{ eff.}}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 % to 80 %  $V_{DS}$ .

## TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Fig. 1 - Typical Output Characteristics,  $T_C = 25^\circ\text{C}$




Fig. 3 - Typical Transfer Characteristics




Fig. 2 - Typical Output Characteristics,  $T_C = 150^\circ\text{C}$




Fig. 4 - Normalized On-Resistance vs. Temperature




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage






Fig. 8 - Maximum Safe Operating Area




**Fig. 9 - Maximum Drain Current vs. Case Temperature**



**Fig. 10a - Switching Time Test Circuit**



**Fig. 10b - Switching Time Waveforms**



**Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case**




Fig. 12a - Unclamped Inductive Test Circuit




Fig. 12b - Unclamped Inductive Waveforms




Fig. 12c - Maximum Avalanche Energy vs. Drain Current




Fig. 12d - Basic Gate Charge Waveform




Fig. 13a - Typical Drain-to-Source Voltage vs. Avalanche Current




Fig. 13b - Gate Charge Test Circuit



## TO-220-1



| DIM. | MILLIMETERS |       | INCHES |       |
|------|-------------|-------|--------|-------|
|      | MIN.        | MAX.  | MIN.   | MAX.  |
| A    | 4.24        | 4.65  | 0.167  | 0.183 |
| b    | 0.69        | 1.02  | 0.027  | 0.040 |
| b(1) | 1.14        | 1.78  | 0.045  | 0.070 |
| c    | 0.36        | 0.61  | 0.014  | 0.024 |
| D    | 14.33       | 15.85 | 0.564  | 0.624 |
| E    | 9.96        | 10.52 | 0.392  | 0.414 |
| e    | 2.41        | 2.67  | 0.095  | 0.105 |
| e(1) | 4.88        | 5.28  | 0.192  | 0.208 |
| F    | 1.14        | 1.40  | 0.045  | 0.055 |
| H(1) | 6.10        | 6.71  | 0.240  | 0.264 |
| J(1) | 2.41        | 2.92  | 0.095  | 0.115 |
| L    | 13.36       | 14.40 | 0.526  | 0.567 |
| L(1) | 3.33        | 4.04  | 0.131  | 0.159 |
| Ø P  | 3.53        | 3.94  | 0.139  | 0.155 |
| Q    | 2.54        | 3.00  | 0.100  | 0.118 |

ECN: X15-0364-Rev. C, 14-Dec-15  
DWG: 6031

### Note

- M\* = 0.052 inches to 0.064 inches (dimension including protrusion), heatsink hole for HVM

## Package Picture





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.